



08.10.2025

SLD 23 -H -H			
Name	Bezeichnung	Value	Unit
p300	Motor type selection	4	
p301	Motor code number selection	0	
p305	Rated motor current	21,80	Aeff
p311	Rated motor velocity	600,00	m/min
p315	Motor pole pair width	28,00	mm
p316	Motor force constant	69,00	N/Aeff
p322	Motor maximum velocity	600,00	m/min
p323	Maximum motor current	82,00	Aeff
p338	Motor limit current	82,00	Aeff
p341	Motor weight	16,50	kg
p312	Rated motor force	512,00	N
p317	Motor voltage constant	34,64	Veff s/m
p318	Motor stall current	21,80	Aeff
p319	Motor stall force	512,00	N
p320	Motor rated magnetizing current/short-circuit current	0,001	Aeff
p325	Motor pole position identification current 1st phase	0,000	
p326	Motor stall force correction factor	100,00	%
p327	Optimum motor load angle	90,00	°
p328	Motor reluctance force constant	0,00	mH
p329	Motor pole position identification current	26,00	Aeff
p348	Velocity at the start of field weakening Vdc = 600 V	660,00	m/min
p391	Current controller adaptation starting point KP	21,80	Aeff
p392	Current controller adaptation starting point KP adapted	82,00	Aeff
p393	Current controller adaptation p gain adaptation	30,00	%
p350	Motor stator resistance cold	0,20	Ohm
p356	Motor stator leakage inductance	2,00	mH
p604	Mot_temp_mod 2: sensor alarm threshold	100,00	°C
p605	Mot_temp_mod 1/2 sensor threshold and temperature value	105,00	°C
p606	Mot_temp_mod 2: sensor timer	1,00	s
p611	I2t motor model thermal time constant	30,00	s
p612.0	Activate mot_temp_mod 1 (I2t)	1,00	
p615	Mot_temp_mod 1 (I2t) fault threshold	100,00	
p1752	Motor model changeover speed operation with encoder	660,00	m/min
p1980	PolID technique	1	
p1981	PolID distance max	30	°