

New

The new SCHUNK Grippers
PGN-plus-P and **PGN-plus-E**
of the Generation **Permanent**.
The only grippers with multi-tooth
guidance and permanent lubrication.



1945 – 2015
70 Years

Superior Clamping and Gripping



Gripping Meets Industry 4.0

Intelligent Gripping Technology
for smart Production Processes



Superior Clamping and Gripping

Jens Lehmann stands for precise gripping, and safe holding. As a brand ambassador of the SCHUNK team, the No. 1 goalkeeper represents our global competence leadership for clamping technology and gripping systems. The top performance of SCHUNK and Jens Lehmann are characterized by dynamics, precision, and reliability.

For more information visit our website:
www.gb.schunk.com/Lehmann

J. Lehmann
 Jens Lehmann





Henrik A. Schunk, Kristina I. Schunk, brand ambassador Jens Lehmann, and Heinz-Dieter Schunk

Top Performance in the Team

SCHUNK is the world's No. 1 for clamping technology and gripping systems – from the smallest parallel gripper to the largest chuck jaw program.

In order to boost efficiency, SCHUNK customers have bought more than 2,000,000 precision toolholders, 1,000,000 SCHUNK grippers, and 100,000 lathe chucks and stationary workholding systems so far.

This makes us proud and motivates us to attain new top performances.

As a competence leader, we recognize and develop standards with a large potential for the future, which will drive the rapid progress in many industries.

Our customers profit from the expert knowledge, the experience, and the team spirit of more than 2,500 employees in our innovative family-owned company.

The Schunk family wishes you improved end results with our quality products.

Heinz-Dieter Schunk

Henrik A. Schunk


Kristina I. Schunk

70 Years of SCHUNK – From a workshop to a global player

1945 Foundation



Friedrich Schunk
Company founder



The lampshade perforating machine –
an innovative development by
Friedrich Schunk

1945 – Early years 1970



1945 The first workforce



Precision parts production
for the Porsche 356



SCHUNK becomes the
first standard chuck jaw
provider in Germany



1964 Heinz-Dieter Schunk
joins the company

1971 – Setting the course 1990

PPG – First
pneumatic
SCHUNK gripper



PGN
Pneumatic
2-finger gripper



TENDO Hydraulic
expansion toolholders



1991 – "Taking off" 2000

PGN-plus
First gripper
with SCHUNK
multi-tooth
guidance



MPG
The new
benchmark in
pneumatic small
parts handling.



Workholding
Technology
product area



1992 Morrisville plant, NC USA

2001 – Growth 2005

SDH – First SCHUNK
3-finger gripping hand



Linear Modules
product area



TRIBOS-Mini
Polygonal clamping
technology for micro
machining



1945 – 2015

70 Years



With Pioneering Spirit and Perfection we are setting Benchmarks worldwide

The challenges that our innovative family-owned company has overcome over 70 years of working with clamping technology and gripping systems are reflected in our top-quality products and technical innovations. They stand as milestones which document our development from a small garage business into a global player with more than 2,500 employees.

They are the result of ambition, courage and the work of many highly motivated contributors with team spirit and incredible dedication to the company. We owe our success to the confidence and trust placed in us by our customers. Their appreciation spurs us on every day to do our best. And this goes for the future as well.

2006 –
New horizons 2008

Integrated PRL
gripping arm
module in the
Care-O-Bot®



2008 First Expert Days
of Service Robotics

JGP
SCHUNK
Compact class



Magnetic
clamping
technology
product area



2009 –
Expansion 2011

Powerball
Lightweight
Arm LWA 4P



2009 New building of the
Hausen gripping
systems plant

EGP
The most powerful
electronic small
component gripper
with integrated
electronics



Launch of
VERO-S
quick-change
pallet system



2012 –
Superior Clamping
and Gripping 2015



The new SCHUNK PGN-plus-P
and PGN-plus-E grippers of
the Generation [Permanent](#).
The only grippers with multi-tooth
guidance and permanent
lubrication.

SVH
First mass
production
5-finger hand
with 9 motors



The first EGN
certified safety
gripping system



Awards!

With a pioneering spirit and perfection we create the developments in clamping technology and gripping systems. Highly recognized and coveted awards, and prizes honor the excellent performance of our company, as well as our SCHUNK team.

We are pleased that we can set benchmarks with our full commitment. We want to take this opportunity to say thank you for the multiple recognitions – at national and international levels.



Dr. Rudolf Eberle Prize
1986 Gripping Systems

EuroMold Award
1998 TRIBOS
2002 SINO-T

Advertising Excellence Award
2002 SCHUNK "Power"-Advertising



iF product design award
1999 TRIBOS
2004 ROTA THW plus
2004 SRU
2005 TANDEM PZS
2009 ZENTRICO THL plus
2011 PHL
2012 ROTA NCL
2015 EGS

Junior Chamber Prize
2005 Junior Chamber Prize
2008 Junior Chamber Prize

Technology Award "Tech-Stars"
2006 3-Finger Dextrous Gripper Hand



Enterprise Medal of the State of Baden Wurttemberg
2006 Heinz-Dieter Schunk

A & D Best Product Award
2007 System GEMOTEC



Industry award
2008 Machine building:
Gripper with spindle interface
2008 SWS-I-011
2010 PPU-E
2012 EGP 40 (BEST OF 2012)
2013 NSR (BEST OF 2013)



MM Award to the AUTOMATICA
2008 Dextrous Hand SDH-2
2010 MPG-plus
2012 Powerball Lightweight Arm LWA 4P
2014 SCHUNK Safety Gripping Systems



German Machine Tool Industry Award
2008 Heinz-Dieter Schunk



Process Innovation Award
2009 UNIPLACE

KE Konstruktion & Engineering
2009 PPU (November 2009)
2010 CFK (August 2010)



Engelberger Robotics Award
2010 Heinz-Dieter Schunk



Bosch Global Supplier Award
2011 / 2012 SCHUNK GmbH & Co. KG



Preferred Supplier of the Bosch Group
2012 SCHUNK GmbH & Co. KG
2013 SCHUNK GmbH & Co. KG



Training Company of the Year Federal Metal Association
2011 SCHUNK GmbH & Co. KG



red dot award
2013 Powerball Lightweight Arm LWA 4P



Founder's Prize of Baden Wurttemberg Savings Bank Finance Group
2013 Heinz-Dieter Schunk



MM Innovation Award – Milestones of industrial History
2015 SCHUNK GmbH & Co. KG

Contents

	Page
Highlights	8
The new SCHUNK Grippers of the Generation Permanent	8
Gripping Meets Industry 4.0	14
SCHUNK e-GRIP Finger Designer	20
SCHUNK Gripping Systems	22
Customized Components and Gripping Systems	23
Gripping Meets Robotics	24
The new SCHUNK Gripper Catalog	30
New Products	31
SCHUNK Grippers	32
Rotary Gripping Modules	40
Rotary Modules	42
Linear Modules	46
Modular Assembly Automation	48
Robot Accessories	52
Modular and Mobile Gripping Systems	58
Accessories	60
SCHUNK No. 1 Products for	64
Your Automated Machine Loading	71
Your Automated Handling System	77
Your Automated Assembly	81
Your Service Robotics Application	87
Your Lathe	93
Your Machining Center	99
SCHUNK Contact	108

The new SCHUNK Grippers PGN-plus-P and PGN-plus-E of the Generation **Permanent**.

With the new SCHUNK grippers PGN-plus-P and PGN-plus-E of the Generation **Permanent**, SCHUNK has improved its tried and tested technology. The new pneumatic SCHUNK PGN-plus-P is distinguished by three innovations: The improved tooth guidance, permanent lubrication with continuous lubricant pockets and maximum force for higher workpiece weights. The SCHUNK PGN-plus-E is the newly developed electrical counterpart of the pneumatic universal gripper. It is also equipped with improved multi-tooth guidance and permanent lubrication, its gripping force is variable in four steps.



Benefit from
the advantages:

- up to **50%**
longer gripper fingers
- up to **120%**
higher finger load


The patented SCHUNK multi-tooth guidance. Proven technology. Now even better!

The new SCHUNK grippers PGN-plus-P and PGN-plus-E of the Generation **Permanent** stem from a unique history of success. They are the result of a sophisticated innovation strategy to continuously expand the proven basic components with state-of-the-art features. In 2000, SCHUNK recognized that the T-slot guide used for many conventional grippers was a weak point. This was when the SCHUNK multi-tooth guidance was born, which makes the SCHUNK PGN-plus universal gripper the world's best gripper.




T-slot guidance. Conventional technology.

The generated forces and torques must be shouldered by **two guideways**. In the process, **considerable load peaks** can arise, which can lead to **premature wear** and **loss in precision**.




SCHUNK multi-tooth guidance. Patented technology.

The patented SCHUNK multi-tooth guidance redefines **precision and durability** in the SCHUNK PGN-plus universal gripper. Forces and torques are distributed to the **guiding areas of several prism guides arranged in parallel**. Therefore, the guides have a **higher bearing capacity** and ensure considerably **better stability**.




SCHUNK multi-tooth guidance. Generation **Permanent**.

We have improved tried and tested technology. With the now improved new multi-tooth guidance for the SCHUNK grippers of the Generation **Permanent**, the **supporting dimension between the six load-bearing shoulders was considerably increased**. The result: **Higher moments** can be accommodated and **longer fingers** are used.



Up to **40%** higher supporting dimensions



■ = longer gripper fingers ■ = higher finger load

The new SCHUNK Gripper PGN-plus-P of the Generation **Permanent**.

With lubrication pockets in the multi-tooth guidance.

With the new SCHUNK gripper PGN-plus-P of the Generation **Permanent**, SCHUNK is once again raising the bar for pneumatically powered universal grippers. Due to consistent optimization of the multi-tooth and force, it sets the new benchmark for the market. At the same time, the PGN-plus-P benefits from the unique SCHUNK accessory program for the nearly complete spectrum of feasible automation applications.





Up to 50% longer gripper fingers – due to higher maximum moments

The improved multi-tooth guidance allows the use of even longer gripper fingers due to higher maximum moments while retaining the same gripper size, without overloading the guidances.

Gripping with optimized interfering contours for spatially constrained handling tasks has been made even easier as a result.



Higher force

With the enlarged surface of the drive piston in the existing and simultaneously compact installation space, the gripping force of the PGN-plus-P is increased. Higher workpiece weights can be handled in relation to the gripper size.




PGN-plus-P Generation
Permanent pneumatic
2-finger parallel gripper



Longest life span due to lubrication pockets in the durable multi-tooth guidance

Lubricant pocket through-holes ensure a permanent supply of lubricant. At the same time, they assure a quick and even formation of a lubricant film, also in the case of short strokes.



Maximum process reliability

The new multi-tooth guidance allows a larger wedge hook surface and therefore lower surface pressure for low-wear transmission of forces to the base jaw for a reliable process.




Diverse accessories

There is a wide range of high-quality accessory components available for SCHUNK PGN-plus-P grippers. Of course, this spectrum includes the right sensors as well as efficient microvalve technology for shorter cycle times and lower energy consumption.



Perfectly coordinated accessories

e.g. ABV microvalves
Shorter cycle times with reduced pneumatic energy consumption.



Wireless sensor systems

Wireless RSS query system
Wireless sensor system for signal and status querying of sensors and processes.

The new SCHUNK Gripper PGN-plus-E of the Generation **Permanent**.

The first easy electric gripper with multi-tooth guidance, digital control and 24 V drive.

The new electric SCHUNK gripper PGN-Plus-E of the Generation **Permanent** applies the proven high-performance features of the PGN-plus-P pneumatic gripper in the area of mechatronic handling. The first simple electric gripper with multi-tooth guidance, digital control, and 24 V drive makes the switch from pneumatic to electric components especially easy. Its digital control via binary signals simplifies commissioning and enables quick integration into existing systems.





Up to 50% longer gripper fingers – due to higher maximum moments

The improved multi-tooth guidance allows the use of even longer gripper fingers due to higher maximum moments while retaining the same gripper size, without overloading the guidances.

The proven diagonal-pull kinematics ensures high surface coverage.




Easy gripping force adjustment

The gripping force of the SCHUNK PGN-plus-E can be adjusted quickly, safely, and manually in four stages.



Longest life span due to lubrication pockets in the durable multi-tooth guidance

Lubricant pocket through-holes ensure a permanent supply of lubricant. At the same time, they ensure a quick and even formation of a lubricant film, also in the case of short strokes.



Maximum process safety

Multi-tooth guidance allows a larger wedge hook surface and therefore lower surface pressure for low-wear transmission of forces to the base jaw for a reliable process.



Integrated sensor system

The control and power electronics are fully integrated, which ensures that no additional space in the switch cabinet is required. The 24 V gripper is actuated via digital I/O inputs. M8 plug connectors query up to 2 gripper positions.




The Mega Trend of Industry 4.0

The term “Industry 4.0” represents an as yet incompletely perceived change in existing production structures and markets. This is because the intermingling of production and information technology within networked factories is creating new forms of wealth creation.

SCHUNK already allows its customers to achieve full potential. Reduction in production costs and set-up times as well as providing efficient, intelligent, mechatronic components from the world’s largest product portfolio. This is also our objective for Industry 4.0. With SCHUNK Synergy, the perfectly matched interplay between clamping technology and gripping systems, we

are showing our customers new approaches to designing more efficient and automated production processes. Even today, intelligent SCHUNK components with networking capability provide the basis for flexible production automation. Of course, in close cooperation with machine builders or system integrators, it goes without saying.

Industry 4.0 Networking




Sustainable Gripping Systems

SCHUNK components achieve more than one task. They supply information. As a partner for end customers, system integrators and machine builders, SCHUNK offers the widest product range for robots and handling solutions capable of delivering information and networking, i.e. Industry 4.0-ready.

The properties are clearly adapted to the needs of industry:

- **Flexibility**
Freely positionable SCHUNK components that are quick and intuitive to adjust.
- **Communication/interface**
SCHUNK components offer a wide range of communication interfaces for networking.
- **Distributed/integrated intelligence**
In this context, SCHUNK is pushing ahead with future topics such as IO-Link and NFC.
- **Mobility**
Energy-efficient drives and components developed with an eye to lightweight construction establish important basic preconditions.
- **Mechatronization**
Components can be used extremely flexibly, allowing a large number of intelligent functions.
- **Human/machine interaction**
SCHUNK components for intuitive start-up by simple configuration.
- **Safety**
Functional safety through certified, safe SCHUNK components.
- **Quality assurance monitoring**
SCHUNK components deliver precise information for quality assurance and for monitoring system parameters and process data.
- **Conversion capability**
Adaptation of the SCHUNK component to the customer's requirement. You benefit from the ability to configure variants right through to complete customer-specific solutions.



Industry 4.0 – Smart Production Processes by using SCHUNK Components

This Industry 4.0 cell shows by way of example how a basic carrier with a gear and a circuit board are assembled to make an assembly group. Here, SCHUNK components with networking and communications capability form the basis for flexible production automation, together with convertible, flexibly

controllable SCHUNK actuators. Together with plug & work-capable, intuitively operable concepts, they offer maximum flexibility for networked production.

Pick & Place Assembly Stations

With standardized pick & place units and modular assembly components

1 Mechatronic – Alternative

1:1 pneumatic replacement by alternative mechatronic SCHUNK components



EGS gripping swiveling unit [Page 40](#)

- Gripping force (15 and 30 N) and angle of rotation (40 – 290°) can be set directly on the module
- Control via 4 digital inputs and 24 V DC



EGP Safety 2-finger gripper for small components

- Certified functional safety with performance level d/SIL 3
- Maintenance of gripping force by safe operating stop (SOS)
- Inner and outer lock in one gripper




2 Pneumatic

SCHUNK sensors make pneumatic components ready for Industry 4.0



MPG-plus 2-finger gripper for small components with SCHUNK MMS-A analog magnetic sensor and IO-Link [Page 84](#)

- Non-contact analog position monitoring of the gripping stroke
- Differentiation between workpieces in the gripping process
- Convenient teach-in within a matter of seconds
- IO-Link in preparation



Inspection and Quality Control Station

SCHUNK components: Linear motor axes with pillar assembly system, torque motor and mechatronic gripper

3 Mechatronic – Intelligent

With intelligent mechatronic SCHUNK components towards the smart factory





ELB linear module

- Absolute or incremental stroke measuring system
- Flexible setting of position, speed and force for handling various workpieces

WSG sensitive 2-finger parallel gripper [Page 38](#)

- Sensitive actuator with force-measuring fingers permits integrated quality control in the handling process
- Integrated intelligence and Ethernet interface



Experience SCHUNK Industry 4.0 applications live on the Internet
www.gb.schunk.com/industry4.0

Packaging Station

SCHUNK components: RPE room gantry with pillar assembly system, rotary table with mechatronic turning unit


4 Mechatronic – Adaptable

Adaptable, mechatronic SCHUNK components permit networked, flexible production



EGA long-stroke gripper [Page 78](#)


- Use of all current servo motors and controllers
- Use of process data for integrated quality assurance
- Parallel or radio adaptation of the motor
- Gripping force and gripping stroke are freely adjustable for efficient individualization



6



2



Robot Assembly Stations

SCHUNK End-of-Arm expertise:
Robot accessories, rotary tables, and rotary modules



5 Mechatronic – Intelligent

Mechatronic SCHUNK components as the basis/
foundation for autonomous systems



EGL 2-finger parallel gripper with IO-Link
Page 36

- Highly flexible in terms of finger position, closing speed and gripping force for an extremely wide range of workpieces
- Complete control and power electronics integrated
- IO-Link in preparation



FTN 6-axis
force/torque sensor

- Simple configuration via web browser
- System connection via Ethernet, DeviceNet or ProfiNet

6 Pneumatic

SCHUNK robot accessories make pneumatic
components that are already in use compatible
with Industry 4.0



SWS quick-change system Page 73

- Quick exchange of tools and effectors increases flexibility
- Ability to carry ProfiNet signals and to change ProfiNet components



Logistics Station

SCHUNK components: High-speed linear axis,
Powerball lightweight arms and mechatronic grippers

7 Mechatronic – Intelligent



LWA 4P Powerball Lightweight Arm Page 90

- 6 degrees of freedom for accurate repetition of movement to any positions in space
- Integrated and distributed intelligence reduces the load on the high-level control unit
- 24 V DC supply allows mobile use with optional battery operation



PG-plus 2-finger parallel gripper

- Vision-capable*, freely adjustable gripper for automatic gripping of workpieces
- Integrated optical quality control in the gripping process by selection of any required camera

* Vision-capable grippers are in preparation.



Gripper Fingers at the Press of a Button.

Online design and webshop order in 15 minutes.

SCHUNK eGRIP is the first fully automatic, web-based 3D design tool for additively manufactured gripper fingers. The browser-based web tool does not require a license and drastically reduces the design and ordering time for tailor-made gripper fingers.

Your advantages with the SCHUNK eGRIP finger designer


- ✓ Delivered in **1 week**
- ✓ **100%** accuracy of fit
- ✓ **50%** cost reduction in gripper fingers



www.schunk.com/egrip




Pneumatic
SCHUNK Gripper
PGN-plus



An example.


With SCHUNK eGRIP you can easily implement **form-fitting finger geometries** – especially those that are difficult or impossible to manufacture with machining processes.



Cast-iron workpiece

Steam boiler for a model railroad locomotive

✓ Upload a part



Simply **upload** the **STEP** or **STL** file for the work-piece. Supply **specific data**, for example the **weight**, the **installation position** of the gripper and the **finger length**.



Pneumatic
SCHUNK Gripper
MPG-plus



Electric
SCHUNK Gripper
EGP



Pneumatic
SCHUNK Gripper
PGN-plus

Online design and
webshop order in
15 minutes



Delivery in
1 week



SCHUNK eGRIP designs custom gripper fingers with the **optimal 3D contour** and a detailed offer including **price and delivery time**.



With SCHUNK eGRIP you receive custom SCHUNK gripper fingers fast.

SCHUNK Gripping Technology

From the Standard Component to the Customized Gripping System


More than 30 years of gripping competence is the basis for the world's largest standardized gripping technology product range with more than 4,000 components and for an average of 2,000 standard and customized gripping systems per year.

Components

Standard Components



SCHUNK Grippers



Rotary Modules



Linear Modules



Robot Accessories



Pick & Place Units



Gripping Hands




Lightweight Arms

Customized Components

From standard components further developed in accordance with customer requirements to exclusive customized new developments.

Examples:



Wafer Grippers

made of laser-forming material with SCHUNK LGP gripper



Compact Vises

for sheet metal machining, pneumatically actuated



Packaging Grippers

High-speed grippers according to legal, hygienic, and production specifications

Gripping Systems

Standard Gripping Systems



Modular Assembly Automation



Line and Room Gantries



Solution composed of several SCHUNK standard components for robots and gantries

Customized Gripping Systems

Solution composed of several SCHUNK components, of which at least one is further developed or newly developed specifically for the customer.

Examples:



Connecting Rod Handling




Aluminum Foil Handling



Modular and Mobile Gripping Systems

From the Standard Component to the Customized Gripping System



Just **1** Expert Contact Person for a Solution from one Source

For smooth communications, a personal contact person is available to you from the start of the project until completion. Your contact person is the interface between you and the individuals involved in the project and ensures that information is exchanged smoothly.

From planning to continued support after the conclusion of the project, SCHUNK guarantees that your project will be handled cooperatively and efficiently.

Your advantage

- Over 30 years of experience in gripping technology
- Over 12,000 implemented gripping systems for a wide range of industries
- Modular design with perfectly coordinated standard components
- Complete accuracy of fit due to standardized interfaces
- Shorter project lead times due to standardized systems
- Reliable implementation processes and planning security without extra project costs
- Functional assemblies fitted on request or ready for use
- Time savings due to the perfect solution from a single source

Gripping Meets Robotics

**Discover SCHUNK End-of-Arm Expertise!
For every Robot, every Industry,
every Handling Task.**

With its components and gripping systems SCHUNK sets standards worldwide in automation for every sector.

Our robot accessories include a uniquely extensive standard range of modules for the mechanical, sensoric, and power connection of handling devices and robots. The comprehensive range of robust and durable gripping modules for small components and universal gripping modules features high product quality, precision, and numerous sensing options.


With axis system handling solutions SCHUNK also opens up new perspectives for optimally priced and value-added automation solutions from a single source.

Take Advantage of the SCHUNK Modular System with more than 4,000 standard Components.



The SCHUNK End-of-Arm E

From the standard Component
to the standard Gripping System.



Expertise ...

... for your
articulated arm robot

Feed-throughs

SCHUNK DDF 2 Rotary Feed-through [Page 85](#)

Connecting

SCHUNK Adapter Plate [Page 82](#)

Monitoring

SCHUNK OPR Collision and
Overload Sensor [Page 78](#)

Joining and Compensating

SCHUNK TCU Compensation Unit
[Page 82](#)

Changing

SCHUNK SWS
Quick-change System
Consisting of SWK (Quick-change
Head) and SWA (Quick-change
Adapter) [Page 73](#)

Gripping

SCHUNK Gripper PGN-plus-P
of the Generation **Permanent**
2-finger universal gripper
with multi-tooth guidance
[Seite 32](#)

... for your
SCARA Robot

Connecting

SCHUNK Adapter Plate [Page 82](#)

Measuring

SCHUNK FT Mini
6-Axis Force/Torque Sensor [Page 82](#)

Changing

SCHUNK HWS Manual Change System
Consisting of HWK (Manual Change System)
and HWA (Manual Change Adapter) [Page 73](#)

Gripping

SCHUNK PZN-plus Gripper
3-Finger Centric Gripper with
Multi-tooth Guidance

[Page 74](#)

... for your
Delta Robot



Changing
SCHUNK SWS Quick-change System
Page 73


Connecting
SCHUNK Adapter Plate
Page 82





Gripping
SCHUNK MPG-plus Gripper
2-Finger Miniature Parallel Gripper
Page 84



Moving
SCHUNK LDN
Linear Axis
Page 83



Connecting
SCHUNK Adapter Plate
Page 82



Gripping
SCHUNK MPG-plus Gripper
2-Finger Miniature Parallel Gripper
Page 84

New

The SCHUNK Gripper Catalog.

The world's most comprehensive gripper portfolio.



Benefit from the benchmark of gripping technology

- ✓ with more than **2,500** standard grippers and more than 300 mechatronic grippers
- ✓ with more than **1,800** pages of compact SCHUNK gripping competence
- ✓ with the **complete** spectrum of proven and highly innovative SCHUNK gripping technology
- ✓ with **15** new series in graduated sizes
- ✓ with world-**leading** technology and a diversity of variants
- ✓ with an **extensive** accessory programme, such as sensor systems



www.schunk.com/catalogorder

New Products

	Page
SCHUNK Grippers	32
PGN-plus P Generation Permanent 2-Finger Parallel Gripper	32
PGN-plus E Generation Permanent 2-Finger Parallel Gripper	34
EGL 2-Finger Parallel Gripper	36
WSG 2-Finger Parallel Gripper	38
Rotary Gripping Modules	40
EGS Rotary Gripping Unit	40
Rotary Modules	42
SRM Universal Rotary Unit	42
ERD Rotary Module	44
Linear Modules	46
DRIVE-CLiQ Transducer	46
Modular Assembly Automation	48
DRL Rotary Pick & Place Unit	48
Pillar Assembly System	50
Robot Accessories	52
FT Mini 6-Axis Force/Torque Sensor	52
FTW Wireless Transmitter	54
SHS Manual Change System	56
Modular and Mobile Gripping Systems	58
Servo-Electric SVH 5-Finger Gripping Hand	58
Accessories	60
ECM Controller	60
SDV-P Pressure Maintenance Valve	62

PGN-plus-P Generation Permanent 2-Finger Parallel Gripper. With Lubrication Pockets in the Multi-tooth Guidance.

Improved multi-tooth guidance and new permanent lubrication

With the new SCHUNK gripper PGN-plus-P of the Generation **Permanent**, SCHUNK is once again raising the bar for pneumatically powered universal grippers. Three technical innovations establish the leading position of the SCHUNK PGN-plus-P. First, there is the improved multi-tooth guidance. By enlarging supporting dimensions between the six load-bearing shoulders of the patented multi-tooth guidance, higher moment can be accommodated and thus up to 50% longer fingers can be used. Secondly, permanent lubrication is provided via the continuous lubricant pockets in the guidance. For short strokes in particular, the principle of a reduced amount of lubricants ensures particularly quick and even distribution of the lubricant such that the gripper is nearly maintenance-free and its service life is extended.

Force all the way to the finger tips

The SCHUNK PGN-plus-P has an enlarged drive piston area, whereby gripping force is increased by up to 50%. The SCHUNK PGN-plus-P benefits from a unique accessory program.

Nearly the entire spectrum of feasible automation applications can be mastered with the reliable performance of the modular system of universal grippers. SCHUNK underscores its Longlife functional warranty, durability, reliability, and precision in the μ -range with the PGN-plus-P. The new gripper benchmark is being introduced in an initial stage in sizes 50 to 125. Expansion to include all existing PGN-plus sizes is planned.

Benefit from the advantages:

- up to **50%** longer gripper fingers
- up to **120%** higher finger load
- up to **50%** higher gripping force



The new SCHUNK Gripper Generation Permanent!

Improved multi-tooth guidance with permanent lubrication, higher maximum moments, and higher force.

Available starting January 2016



Sizes
50 .. 125



Weight
0.17 kg .. 1.35 kg



Gripping force
160 N .. 2780 N



Stroke per finger
2 mm .. 13 mm



Workpiece weight
0.8 kg .. 13.9 kg

Product features


- Improved SCHUNK multi-tooth guidance with a larger supporting dimension
- Increased maximum moment and force
- Lubricant pockets with flat lubricating wedge in the multi-tooth guidance
- Larger drive piston areas
- Improved efficiency and wear reduction
- Precise repeat accuracy 0.01 mm

Your advantage

- Up to 50% longer gripper fingers due to higher maximum moments
- Handling of higher workpiece weights with up to 50% higher gripping force
- Rapid and even lubricant distribution even with short strokes.
- Reduced total cost of ownership (TCO)
- Permanently higher performance
- More compact, efficient systems
- Continuously reliable and robust

Function cross section

- 1 Multi-tooth guidance
- 2 Base jaw
- 3 Sensor systems
- 4 Housing
- 5 Centring and mounting options
- 6 Wedge hook principle
- 7 Piston drive



PGN-plus-E Generation Permanent 2-Finger Parallel Gripper. The first simple electric Gripper with Multi-tooth Guidance, Digital Control and 24 V Drive.

Mechatronic universal genius

With the new SCHUNK gripper PGN-plus-E of the Generation Permanent, SCHUNK is applying the performance package of its new pneumatic universal gripper SCHUNK PGN-plus-P directly to the area of electric handling applications. Like its role model, the SCHUNK PGN-plus-E also has improved multi-tooth guidance for the accommodation of higher moment, a lubricant pocket through-hole in the guidance contour, and the proven diagonal-pull kinematics with a high surface coverage in all stroke positions. The mechatronic universal gripper is powered by a brushless DC servo motor. Therefore, permanently high process stability and a long service life with minimal maintenance requirements are ensured. The SCHUNK PGN-plus-E benefits from a unique accessory program. Nearly the entire spectrum of feasible automation applications can be mastered with the reliable performance of the modular system of universal grippers.

Fully integrated control and power electronics

The mechatronic universal gripper makes the switch from pneumatic to electric components particularly easy: it has an identical screw connection pattern to its pneumatic counterpart, and the 24 V gripper is easily controlled via digital I/O. Up to two gripping positions can also be monitored by means of an additional M8 standard connection. The necessary control and power electronics are already fully integrated in the compact module, so no additional space in the switch cabinet is required. Neither extensive mechatronic know-how nor additional programming is necessary for commissioning. The gripping force of the SCHUNK PGN-plus-E can be adjusted in four stages. The grippers will initially be available in size 80. Additional sizes are planned.

Benefit from the advantages:

- up to **50%** longer gripper fingers
- up to **120%** higher finger load
- **easy digital control and gripping force adjustment**



Up to **50%** longer gripper finger –
due to higher moment load

The new electric SCHUNK Grippers of the Generation Permanent!

Proven multi-tooth guidance with permanent lubrication, higher maximum moments, and adjustable gripping force.

Available starting January 2016



Size
80



Weight
1.0 kg



Gripping force
up to 500 N



Stroke per finger
8 mm



Workpiece weight
up to 2.5 kg

Product features


- Fully integrated control and power electronics
- Gripping force adjustable over four stages
- Improved SCHUNK multi-tooth guidance with a larger supporting dimension
- Increased maximum moment and force
- Lubricant pockets with flat lubricating wedge in the multi-tooth guidance
- Brushless DC servo motor
- Proven diagonal-pull kinematics with higher surface coverage in the limit positions
- Improved efficiency and wear reduction
- Precise repeat accuracy of 0.01 mm

Your advantage

- Simple commissioning and quick integration into existing systems
- Up to 50% longer gripper fingers due to higher maximum moments
- More space in the switch cabinet, because no external controllers are used
- Handling of higher workpiece weights with up to 50% higher gripping force
- Fast and even distribution of lubricant, also in the case of short strokes
- Reduced operating costs (TCO)
- More compact, efficient systems

Functional cross section

- 1 Multi-tooth guidance
- 2 Base jaw
- 3 Sensor systems
- 4 Housing
- 5 Centring and mounting options
- 6 Wedge hook principle
- 7 Spindle nut
- 8 Drive
- 9 Control electronics



EGL 90 2-Finger Parallel Gripper. Intelligent Powerhouse for Handling and Assembly.

Optimal combination of power and intelligence

The SCHUNK EGL 90 2-finger parallel gripper, with a variable gripping force between 50 and 600 N is one of the most powerful and flexible mechatronic grippers on the market. Since the finger position, closing speed, and gripping force are freely programmable within a maximum stroke of 49 mm per finger, diverse components up to 3 kg can be precisely handled and are force-fit gripped. The gripper fingers can be prepositioned to reduce cycle times. A brushless servo motor ensures continuous and reliable operation with no maintenance required. To maintain the position in the event of a power outage the gripper features an electrically operated brake.

Fast commissioning

The entire control and power electronics of the EGL 90 are integrated to save space and to allow decentral operation and even mobile use, due to the 24 V DC operating voltage. Standard Profibus DP and CAN bus interfaces allow fast and easy integration in higher level system controllers. The gripper also features a USB-port as a service interface. Since the EGL 90 fulfills industrial standards and the basic version is connected only by means of industrial connectors, installation time is reduced to a minimum.



Highly flexible!

Intelligent powerhouse with variable gripping force adjustment.

Immediately available



Size
90



Weight
1.8 kg



Gripping force
50 N .. 600 N



Stroke per finger
49 mm



Workpiece weight
3 kg

Product features


- Freely programmable finger position, closing speed, and gripping force
- Pre-positionable gripper fingers
- Completely integrated control and power electronics
- 24 V DC operating voltage
- Mobile use possible
- Standard interfaces Profibus DP and CAN bus
- Service interface with USB-port
- Brushless servo motor

Your advantage

- Fast and easy integration in higher level system controllers
- Long-term reliable operation with no maintenance costs
- Reduced assembly time due to industrial standards

Function cross section

- 1 Control electronics
- 2 Encoder
- 3 Electric brake
- 4 Drive
- 5 Kinematics
- 6 Service window



WSG-25 2-Finger Parallel Gripper.

The smallest intelligent Gripper on the Market with control via Ethernet TCP/IP.

Intelligent and sensitive compact gripper

The new WSG 25 small component gripper is the smallest intelligent gripper on the market that can be controlled via Ethernet TCP/IP. The WSG 25 was designed especially for use on small robots and in compact gantry systems. Both the finger position and the gripping force can be individually adapted for each stroke and continuously monitored. Even fragile small components can be handled with assured process stability. Like all grippers of the WSG series the WSG 25 can be put into operation quickly and easily by means of an intuitive user interface via Ethernet TCP/IP and any standard web browser, without the installation of additional software.

For this purpose it is equipped with an industrial M8 connector. The web server is already integrated in the gripper as a standard feature. It can also be used for remote diagnosis and for sending status e-mails.

Complete series – intuitive, integrated, intelligent

The intelligent mechatronic grippers of the WSG series are available in a total of four versions: The WSG 50 version can be controlled either via Ethernet TCP/IP, Profibus, CAN bus or eight virtual digital I/Os. In addition to the basic version WSG 050-110 with a stroke of 55 mm per finger, there is the long-stroke version WSG 050-210 with a stroke of 110 mm per finger. The WSG 32 on the other hand is substantially more compact and was designed especially for the handling of small and medium-sized components.



Very compact!
Only 25 mm wide!

Immediately available



Sizes
25 .. 50



Weight
0.32 kg .. 1.6 kg



Gripping force
5 N .. 80 N



Stroke per finger
32 mm .. 105 mm



Workpiece weight
0.1 kg .. 0.4 kg

Product features


- Optionally with ProfiNet, CAN bus, or Ethernet interface
- Integrated gripping control with web server and in some cases Micro SD card
- Integrated sensor ports in the jaws for optional force-measuring jaws for sizes 32 and 50
- Gripped part monitoring already integrated

Your advantage

- Interface flexibility also when integrating into future systems
- Convenient configuration and diagnostics without software installation directly via Ethernet
- Direct gripping force feedback without interfering sensor system cables
- Implementation of safe processes without additional programming effort

Function cross section

- 1 Base jaw
- 2 Integrated control and power electronics for decentral control of the servo motor
- 3 Bevel gear stage
- 4 Drive
- 5 Power + Ethernet connectors



EGS Rotary Gripping Unit.

The world's most compact electric Rotary Gripping Unit.

The new efficiency class in small component handling

The SCHUNK EGS electric rotary gripping unit makes the switch to pneumatic handling solutions easy. It is the first unit to combine electric gripping and rotation in a single compact housing. The low-maintenance and attractively priced module paves the way for highly efficient pneumatic-free systems. Coupling of the gripping and rotation gear, patented by SCHUNK, allows continuous rotation without an electric feed-through. The module is equipped with stationary, brushless and therefore wear-free 24 V DC motors. It requires no moving cables, slip rings or shock absorbers, which increases the process stability and availability of assembly systems.

Extremely easy commissioning

Both the angle of rotation and the gripping force can be adjusted independently of each other directly at the module. Monitoring is possible via inductive proximity switches. The module is controlled directly/digitally or via a fieldbus distributor. The entire control and power electronics for decentral control of the motors are integrated directly in the module. This eliminates the need for external controllers and additional programming. The SCHUNK EGS features a torque of 0.04 Nm and a freely definable angle of rotation between 40° and 290°. The gripping force is 30 N, the stroke/jaw 3 mm. The swiveling time is 0.18 s/180° and the gripping time is 0.05 s/stroke.



product
design
award



Fast!

The swiveling time amounts to 0.18 s/180°, gripping time is 0.05 s/stroke.

Immediately available



Size
25



Gripping force
30 N



Stroke per jaw
3 mm



Torque
0.04 Nm



Workpiece weight
0.15 kg

Product features


- Small dimensions of 58 mm x 45 mm x 89 mm
- Backlash-free pre-loaded junction roller guides for high-precision gripping and virtually constant gripping forces over the entire finger length
- Swiveling time 0.18 s/180°
- Gripping time 0.05 s/stroke
- Freely definable angle of rotation between 40° and 290°
- Brushless 24 V DC motors
- 4 digital inputs (open gripper, close gripper, rotate left, rotate right)
- Controlled with 24 V

Your advantage

- Fast conversion to pneumatic-free handling
- Convenient configuration without external controllers and additional programming
- Gripping and rotating with one extremely compact module
- Easy, fast commissioning

Function cross section

- 1 Base jaw
- 2 Junction roller guide
- 3 Monitoring
- 4 Drives
- 5 Control electronics
- 6 Patented gear coupling



SRM Universal Rotary Unit. The most powerful Rotary Unit on the Market.

Larger center bore and maximum flexibility

The SCHUNK SRM universal rotary unit ensures high performance for production automation and differs significantly even in external appearance from the existing rotary modules on the market. The most striking features are the low interfering contour, the specially developed internal high-capacity dampers for maximum performance in a compact space and the large center hole for the feed-through of cables, hoses, workpieces or for the use of a camera. To speed up commissioning, the SRM features a pre-defined shock absorber stroke and fast clamping of the end position. In addition, a marking facilitates setting of the angle of rotation. Correspondingly compact, it ensures a customized design at a cost-effectiveness ratio that is unique on the market.

Maximum compact performance

Equally convincing are the internal values: the SRM clearly outperforms comparable benchmark models with better torque, moment of inertia, and rotating time. With the SRM, for example, it was possible to increase the already high torque of the SRU-plus by another 25%. The increased mass moment of inertia is just as impressive: the compact SRM 16, for example, can rotate loads three times higher than the likewise high-end SRU-plus 20. The screw connection pattern of the new high-performance module is accordingly large and robust. SCHUNK optionally offers an air feed-through for compressed air or gases as well as an electric rotary feed-through for the reliable feed-through of sensor and actuator signals. It also offers the possibility of inductive monitoring.



Everything goes through!
Up to 55% larger center hole.

Available from the second quarter 2016



Sizes

16
32
40

m

Weight

0.6 kg
3.0 kg
5.5 kg

M

Torque

1.5 Nm
12 Nm
25 Nm



Center bore diameter

10.5 mm
21 mm
26 mm



Repeat accuracy

0.05°
0.05°
0.05°

Product features


- Enlarged center hole
- Larger and more robust flange screw connection pattern
- Different damper types for a broad range of applications
- Numerous options: air feed-through (MDF), electric feed-through (EDF), inductive monitoring
- Calibration marking for angle of rotation
- End position clamping for process reliability

Your advantage

- Better mass moment of inertia range enables applications with smaller modules.
- Very compact design with internal shock absorbers. Minimized interfering contour
- Highly flexible due to modularity
- Angle of rotation marking simplifies commissioning
- Easy, fast commissioning

Function cross section

- 1 Housing made of press-drawn section
- 2 Robust flange screw connection pattern with large center hole
- 3 Calibration marking
- 4 Hydraulic shock absorber
- 5 Double piston drive



ERD Rotary Module.

The only Torque Motor with integrated Air Feed-through and Absolute Stroke Measuring System on the Market.

Complete module SIL 2-certified

The SCHUNK ERD rotary module is the first endlessly rotating and SIL 2-certified miniature module especially designed for assembly applications in the electronics, consumer goods and pharmaceuticals industries. It is equipped with two integrated air feed-throughs, four electrical feed-throughs, and a SIL 2-certified absolute stroke measuring system. The module makes it possible to implement space-saving, high-torque, high-speed assembly systems that even meet the demanding requirements of the new machinery directives. The rotary module is driven by a brushless synchronous motor with permanent excitation.

Time saving on system restart

Its special geometry ensures high dynamic properties and acceleration. In addition, pneumatic actuators connected to it can be actuated faster because of the optimized air feed-throughs. Both factors taken together ensure short cycle times and high productivity. The absolute-value transducer means that there is no need for time-consuming reference runs either when starting up or after an emergency off; furthermore, the repeat accuracy, specified as 0.01°, also benefits. A large number of pole pairings in the module ensures that it generates a high rated torque of up to 1.2 Nm even at low RPM values. The module has a long service life because it contains hardly any wearing parts.



With absolute stroke measuring system!

Use in functional safety areas up to SIL 2.

Immediately available



Sizes
04 .. 12



Nominal torques
0.4 Nm .. 1.2 Nm



Repeat accuracy
0.01°



Air feed-through
2



Electrical feed-through
4

Product features


- Endlessly rotating miniature module
- SIL 2-certified
- Absolute stroke measuring system with SIL 2-certification
- Pneumatic and electrical feed-throughs
- Brushless synchronous motor with permanent excitation
- Large number of pole pairings
- Bosch-Rexroth IndraDrive CS or IndraDrive Advanced drive control units
- Optionally available in protection classes IP40 or IP54

Your advantage

- High acceleration due to special motor geometry
- Shortest cycle times due to high dynamics
- No reference runs when starting up the system or after emergency stop situations due to an absolute stroke measuring system
- Faster actuation of the actuator in high-speed applications because of optimized air feed-throughs

Function cross section

- 1 Motor connector
- 2 Absolute-value transducer connection plug
- 3 Primary part
- 4 Secondary part
- 5 Air and electrical feed-throughs
- 6 Screw connection




DRIVE-CLiQ Transducer. The modular Transducer System now for SCHUNK Linear Motor Drives.

Now four transducer types

SCHUNK is increasingly opening up its product world towards SIEMENS. Users of the SCHUNK LDx linear module series, SCHUNK PPU-E 15 electric pick & place unit and the SCHUNK ELB linear axis can immediately benefit from the SIEMENS DRIVE-CLiQ classification mark. Four transducer interfaces: SSI, Hiperface, 1 Vss, and DRIVE-CLiQ, are now available for the uniquely broad portfolio for linear motor drives.

Error-free configuration of the drive system

The direct connection to SIEMENS controllers enables a standardized transducer housing to be used. The significant simplification of axis integration with SIEMENS controllers means that the additional SME force/torque sensor system controller can be dispensed with. Furthermore, users benefit from the advantages of simpler start-up, because the SCHUNK components with DRIVE-CLiQ interface have an electronic name plate. This stores the component-specific data allowing error-free configuration of the drive system during start-up.



Free choice!

Four transducer types, SSI, Hiperface, incremental and DRIVE-CLiQ.

Available starting January 2016

DRIVE-CLiQ

Product features


- Standardized transducer housing matching SCHUNK LDx, SCHUNK PPU-E 15 and SCHUNK ELB
- Standardized plug connectors M12
- Motor temperature line is supplied to the transducer line via SCHUNK cable sets.

Your advantage

- Saving on an additional force/torque sensor system controller
- Significant simplification of axis integration on SME controller

Function cross section

- 1 Vss transducer
- 2 SSI transducer
- 3 Hiperface transducer
- 4 DRIVE-CLiQ transducer
- 5 Short-stroke axis with linear motor drive and junction roller guides



DRL Rotary Lift Unit. Implement and turn in confined Spaces. Now also with Center Position.

High-speed assembly with integrated rotary motion

The SCHUNK DRL 25 pneumatic rotary lift unit is a pacemaker for modular high-performance assembly. The rotary loader enables dynamic and yet steady pick & place operations with rotating angles of either 90° or 180°. The 180° version is now available with center position. This means the rotary movement can be stopped at 90° if the deposit station is not yet ready, e.g. to reject faulty parts or simply to move out of the machining area.

High automated system productivity

Up to 75 cycles per minute at minimal loads and a rotating angle of 180°. In contrast to conventional pick & place units assembled from two linear units, the rotary lift unit can be positioned between the pick and place positions. This permits the overall automated system to have a very compact design.



Adjustable angle of rotation!
Center position at 90°.

Immediately available



Sizes

20

25



Max. rotation angle

90° bzw 180°

90° bzw 180°



Vertical stroke

33 mm

40 mm



Driving force

245 N

321 N



Torque

2.26 Nm

3.70 Nm

Product features

- Center position at 90° optimal
- Transferring and turning in one operation
- Rotating angle can be adjusted by $\pm 2^\circ$ on either side
- Vertical end position can be adjusted by 10 mm on either side
- Various pick and place heights are possible
- Two waiting positions are possible by control

Your advantage

- Significantly greater productivity because of higher cycle times
- Greater process reliability because of highly flexible control
- Fewer shock absorbers than in comparable pneumatic solutions
- Additional cycle movement by center position

Function cross section

- 1 Center position
- 2 Vertical drive
- 3 Rotary drive
- 4 Assembly connection
- 5 Connecting member



New modules for the SCHUNK Pillar Assembly System. Greater Flexibility and simple Adjustment of the Handling Units.

More than 10,000 possible combinations


SCHUNK offers the most extensive range of modules in the world for high-performance assembly. The heart of the design is the pillar assembly system that is unique in scope with numerous standardized pillar profiles, adapter plates, centering and connection elements. New assembly sections and innovative media routing now expand the possible applications of the system. With the new modules in the SCHUNK pillar assembly system, it is now possible to achieve complete ranges more cost effectively and economically without sacrificing flexibility and precision.

Quick and easy media routing from the modular system

By integrating various standard elements into the modular system, SCHUNK now offers all media routing possibilities. For one thing, hoses and cables can be routed directly through the pillar. For another, these can be clipped onto the pillars in a time-saving and reliable process.

More versatile and more economical

The SCHUNK APEA mounting plate allows compact structures even directly above a single pillar. The SCHUNK AMEH/AMDH and SCHUNK AMEV/AMDV mounting plates, for their part, extend the already highly versatile range of combination options in the modular system. In the SCHUNK AMEH/AMDH, the mounting surface is arranged horizontally and at right angles to the pillar. In the SCHUNK AMEV/AMDV, the mounting surface is vertical and thus arranged parallel to the pillar. The SCHUNK STG split set collar which facilitates the complete assembly is also new. Fitted below the elements, it can be used for fine positioning of the height of the elements by means of screws. The set collar is in two pieces and can be reused for other positions afterwards. All elements are equipped with additional threads to make the assembly more versatile. This means brackets, cable ducts or those clamps can be attached during set-up.



Even more economic now!
Modules for greater flexibility.

Available starting November 2015



Pillar diameter
20 .. 55 mm



Number of module elements
19

Product features structural element

- Further structure can be attached in parallel, at right angles or directly above the pillars, depending on the structural element
- Ground and hard-chromium plated steel pillars
- Precise shape and positional tolerances
- Three pillar diameters $\varnothing$ 20, 35, and 55 mm
- Assembly and centering holes for simple and precise fitting exchange
- Additional thread for mounting further elements such as brackets, cable ducts or hose clamps


Product features media routing

- Simple and ingenious system for handling modules
- For pillar diameters $\varnothing$ 35 and 55 mm

STG




APEH




AMEH




AMDH



AMEV



AMDV



Media routing



Media routing



FT Mini 58 6-Axis Force/Torque Sensor. Very compact Measuring at a high Signal Quality.

Mini interfering contour

The very compact SCHUNK FT Mini 58 6-axis force/torque sensor is particularly suitable for robot-controlled applications in industrial production, in testing, and verification applications, and in surgical applications. With an outer diameter of 58 mm and a height of 30 mm, it enables precise load measurement up to $\pm 2,800$ N and 120 Nm with minimal spatial requirements. The evaluation can take place via Ethernet, DeviceNet, ProfiNet, DAQ card, etc. Since the sensor also enables highly dynamic control concepts with real-time evaluation, it can be used for the automation of demanding tasks.

For highly dynamic control concepts

Like all SCHUNK force/torque sensors, the SCHUNK FT Mini 58 is equipped with silicon strain measurement gauges. The signal that they provide is 75 times as strong as that of conventional strain measurement gauges, thus ensuring a high signal quality with signal noise reduced to virtually zero. In combination with standard built-in temperature compensation, the high measurement precision in the process is reliably maintained over a wide temperature range. In addition, a high overload factor of up to 21 times that of the maximum force protects against damage.



High signal quality!
Virtually zero signal noise.

Immediately available



Size
Mini 58



Measuring range F
 F_{xy} 700 N .. 2800 N
 F_z 1700 N .. 6800 N



Measuring range M
 M_{xyz} 30 Nm .. 120 Nm



Centre bore diameter
9.5 mm

Product features


- Central through-bore for feed of cables, hoses, or tools
- 6 independent load measuring areas for comprehensive sensor systems
- Available in three protection ratings: IP60, IP65, and IP68
- Evaluation via Ethernet, DeviceNet, ProfiNet, DAQ card, or analogue

Your advantage

- Safe functionality with overload capacity of up to 21 times
- Reliable measuring results with temperature compensation
- Very high signal quality with a signal-noise ratio close to zero

Functional cross section

- 1 Silicon strain gauges
- 2 Robot-compatible cable with axial or optional radial outgoing line
- 3 Stainless steel housing
- 4 Optionally available with protection rating IP60, IP65, or IP68



SCHUNK FTW Wireless Transmitter. WLAN Transmitter for Force/Torque Sensors.

Wireless data transmission

The convenient SCHUNK FTW wireless transmitter was particularly developed for the SCHUNK FT-Nano and SCHUNK FT-Mini 6-axis force/torque sensors. It wirelessly transmits the data of the sensors for data collection, real-time regulation, or user-defined signal processing to system control units or other computers. For the first time, the battery-operated transmitter enables the wireless use of force/torque sensors for mobile robots and platforms in service robotics or intralogistics.

Easy integration in existing WLAN systems

The SCHUNK FTW is standardized in two sizes and the data of up to three or up to six sensors can be transmitted simultaneously. Since communication is done according to the proven IEEE 802.11a/b/g/n standard (2.4 GHz or 5.0 GHz), the transmitter can be easily integrated in existing WLAN structures. The typical signal range is 30 m in an office environment and a range of up to 100 m is possible outdoors.



Powerful!

Data transmission of up to six force/torque sensors simultaneously.

Immediately available

Sizes
2



Number of sensors
Up to 6



Transmission range
Up to 30 m

Product features

- Two configurations available: for up to 3 sensors or up to 6 sensors
- Transmission via WiFi
- Signal range of up to 30 m
- Supply voltage of 24 V

Your advantage

- Transmission via WLAN enables simple integration in existing WLAN systems
- Wireless transmission for mobile application

Accessories

- 1 Battery charger
- 2 FT sensor with cable



SHS Manual Change System. With integrated Monitoring of Locking and Presence Control.

Manual changing system with extensive equipment

The SCHUNK SHS quick-change system sets a new standard for manually operable tool changers for robots. It has a space-saving locking mechanism and offers numerous possibilities for the feed-through of air, vacuum, and signals. A large number of air feed-throughs in relation to the size, which can be connected both axially and radially, opens up ample leeway in system planning. Large cross-sections also ensure a high air flow and quick actuation of the actuators. In the process, special gaskets ensure a seal that is so tight that the system can also be used for the connection of a vacuum.

Extensive line of options

The SCHUNK SHS can be optionally equipped with an integrated tool presence control and a locking query. Various electrical feed-throughs from the SCHUNK standard programme can be connected for the delivery of signals to the modules by means of a flange provide as standard equipment. The non-corrosive manual changing system is available in six sizes (40 to 125) with four to 12 air feed-throughs. It is equipped with hole patterns for S10 flanges for simple assembly on the robot arm. SCHUNK has expanded its portfolio for quick-change tools with this series.



Robust!

Non-corrosive lock bolt and with ISO flange pattern.

Available from the second quarter 2016



Sizes
40 .. 125



Handling weight
up to 75 kg



Moment load
up to 320 Nm



Air feed-throughs
4 .. 12



Repeat accuracy
< 0.02 mm

Product features


- Integrated monitoring of locking and presence monitoring
- Integrated air feed-throughs
- Non-corrosive as standard
- ISO flange pattern

Your advantage

- Feeding through of compressed air and vacuum possible with special gaskets
- Comfortable operation even in the most constrained spaces with hinged locking lever

Functional cross section

- ① Hand lever for intuitive locking and unlocking
- ② Integrated lock monitoring
- ③ Non-corrosive lock bolts
- ④ Integrated air feed-throughs



SVH Servo-electric 5-Finger Gripping Hand. The first industrial 5-Finger Hand.

Integrated control unit in the wrist

The industrial version of the anthropomorphic SCHUNK SVH 5-finger hand grips nearly as perfectly as the human hand. The electronics are completely integrated into the wrist, which allows the 5-finger hand to simulate nearly all human hand movements. Due to the moving parts with a total of nine drives, various gripping operations can be executed with high sensitivity.

Reliable holding

Elastic gripping surfaces ensure a reliable grip on objects. Due to its compact dimensions, the SCHUNK SVH is suitable for gripping and manipulation tasks, and especially for human/robot communication by means of gestures.



Integrated electronics
in the wrist

Visionary!

A vision becomes reality.



Left and right gripping hand



Gripping hand



Key grip



Precision grip



Power grip

Immediately available

Size
1



Weight
1.3 kg

Product features


- Available in left- or right-hand versions
- Low energy consumption at 24 V DC
- Complete integration of control, regulator and power electronics in wrist

Your advantage

- Suitable for mobile fields of application
- Gripping hand key grip, precision grip, power grip
- Easy connection with market-standard industrial and lightweight robots via defined interfaces

Function cross section

- 1 Distal index finger drive for controlling two axes
- 2 Proximal index finger drive is DC motor with spindle drive
- 3 Slip-resistant elastic gripping surface made of rubber for secure holding
- 4 Integrated electronics for direct mounting on the robot arm
- 5 Thumb with two degrees of freedom for bending and pivoting the thumb



ECM Controller. Modular 24/48 V Controller for SCHUNK Modules.

Fast and simple commissioning

The modular controller ECM has been developed specifically for electrically driven gripping and rotary modules with an input voltage of 24 V or 48 V. Equipped with standardized plug connections, it can be quickly and easily connected. Control can be provided via Profibus (up to 12 Mbit/s) or CAN bus (up to 1 Mbit/s). With immediate effect, a ProfiNet interface is available as an additional option. For commissioning and parameterization via PC with the SCHUNK Motion Tool, the ECM has a USB device connection. Alternatively it can also be put into operation in seconds without connecting a programming device. To do this, a USB stick can be parameterized and addressing is done manually via an easily configurable rotary encoding switch.

Everything in view and under control

Initial module movements can be realized via a DIP switch. The ECM is also equipped with an LED and 7-segment display for status display and error analysis. It is also available with four digital inputs and outputs. It is suitable for evaluating resolvers, encoders with an index, differential encoders and absolute-value transducers (SSI, EnDat), and in particular, enables the control of SCHUNK EGN and EVG grippers as well as the SCHUNK ERS rotary module.



Convenient!

Parameterization via USB stick.

Immediately available

Feed line current
max. 15 A



Transmission rate
Profibus max. 12 Mbit/s
CAN bus max. 1 Mbit/s

Product features

- Service interface USB host and two rotary encoding switches
- Standardized plug connections for communication and cage clamp terminals for power
- DIP switches with first test and commissioning functions
- Clear information on current controller status via 7-segment display and 4 LEDs
- Toolfree connection of cables with spring clips and plug connectors

Your advantage

- Fast and convenient manual commissioning
- Substantially simplified assembly
- Maximum interface flexibility due to Profibus, CAN bus, 4 digital I/Os and ProfiNet (2014)

Function cross section

- 1 Status display
- 2 Service Interfaces
- 3 Rotary encoding switch
- 4 DIP switch
- 5 M12 plug connection for communication
- 6 Cage clamp terminals and plug connector



SDV-P Pressure Maintenance Valve. First Pressure Maintenance Valve with manual Air Bleed. Now also with Hose-free Direct Connection.

With hose-free direct connection for PGN-plus 64, 80, 100 and 125

The SCHUNK SDV-P pressure maintenance valve with integrated quick air bleed is available with hose-free direct connection for the screw connection pattern of the PGN-plus 100. Now, SCHUNK is broadening the series to PGN-plus 64, 80 and 125. This means the SCHUNK SDV-P can be linked to all grippers of the PGN-plus platform in these sizes such as PWG-plus, DPG-plus and JGP. The integrated quick-action ventilation minimizes the actions to be taken and prevents wear to both the hoses and the fittings. The SDV-P offers two advantages over grippers with mechanical means for maintaining the gripping force: it has a much more compact design and ensures that the actuators remain in their position immediately in case of an emergency stop, even if the gripper is not yet fully closed.

Reliable

Without having to disconnect the grippers under pressure, the actuators in the defined limit position can easily and quickly be released via the integrated ventilation button of the SDV-P during the reset of the system. The two adjacent ventilation buttons are accessible from the front side and can be actuated easily with a pen, Allen key, etc. The pressure maintenance valves of the SDV-P series ensure a maximum pressure drop of 0.1 bar per hour (at the defined reference volume and constant temperature) and cover a pressure range of 0.5 to 10 bar. The switching time is approximately 10 ms. Existing SDV-P valves without ventilation can be replaced 1:1 with the new SDV-P valves featuring integrated quick-action ventilation.



Manual air bleed!

Without disassembly of the gripper.

Available starting November 2015



Sizes
04 .. 10
64 .. 125



Max. flow
200 l/min .. 800 l/min
200 l/min



Air connection
G1/8
direct



Max. operating pressure
10 bar
10 bar

Product features


- Integrated manual air bleed
- Compact design
- Replace of existing SDV-P is possible with no modification whatsoever
- Convenient access to ventilation buttons from the front
- Suitable for PGN-plus, DPG-plus, PWG-plus, and JGP

Your advantage

- No loss of clamping force in case of pressure drop
- No additional hoses necessary
- Saves time during ventilation of the handling components
- Higher process reliability, since no disconnected hoses can be mixed up

Function cross section

- 1 Quick exhaust
- 2 External air connection to gripper
- 3 Valve tappet
- 4 Direct air connection to gripper
- 5 PGN-plus screw connection pattern



Superior Clamping and Gripping

It's time to use your machine's

With superior components, find potentials in your machine, where you would least expect to find them.

**Make full use of your machine's potential –
with the extensive product portfolio from SCHUNK.**

SCHUNK, the competence leader for clamping technology and gripping systems, can now open up the full potential of your processing machines and production processes. Reduce costs by combining accurate, flexible workpiece machining with dynamic production automation.

SCHUNK Synergy – when everything fits together.

With SCHUNK Synergy, you benefit from superior components from our innovative family-owned company and the result of a perfectly harmonized interplay of clamping technology and gripping systems. The more SCHUNK, the more efficient it is.

full potential!



"Clamping technology and gripping systems – the perfectly adjusted interplay makes you a champion in terms of productivity. We call it SCHUNK Synergy."

Let's have a look where the potentials in your machines are hidden."


Jens Lehmann

SCHUNK No. 1 Products for higher Productivity ...



Discover new
potential now:

www.gb.schunk.com/machine-potential

And order the SCHUNK Synergy poster
by telephone +49-7133-103-2256

... in your Automated
Handling System

up
to **20** tons load
handling
MAGNOS Magnetic lifting technology

... in your Lathe

... in your Lathe

60 seconds
jaw change

Lathe chucks **ROTA-S_{plus} 2.0** and
ROTA THW_{plus}



300% better
surface quality

TEINblo^{TURN} – innovative hydraulic expansion
toolholders, for lathes and turning/milling centers



1,200 standard
chuck jaws

The world's largest chuck jaw program
for every chuck type



... in your Automated Handling System



No. 1 unique

PGN-plus-P, Generation **Permanent**, the only gripper with multi-tooth guidance and permanent lubrication



more **than 500** standard combinations for line and room gantries from the modular system

100% cycle increase

Universal rotary module SRU-plus 20-S, the new benchmark in top performance



90% faster gripper change

SWS Quick-change system – fully automatic gripper change within seconds



... for your Automated Machine Loading

... for your Automated Machine Loading



300 kg load capacity

NSR Robot coupling for pallet handling – space-saving and extremely flexible

100% control

TANDEM KSP plus Clamping force block with jaw monitoring



30% more productivity

Automated machine loading with PGN-plus-P, Generation **Permanent** grippers with GSW Spindle interface

... in your Machining Center



90% less set-up costs

with **VERO-S**, due to set-up during processing time




20 mm height

VERO-S NSE *mini* – the pneumatic quick-change pallet system in a very flat design

... in your Automated Handling System



... in your Machining Center



... in your Automate



75,000 customer-specific solutions

Hydraulic expansion technology for tool or workpiece clamping

100% encapsulated

KONTEC KSK Centric clamping vise fully functional in harsh environments



5-sided workpiece machining

in one set-up – MAGNOS Magnetic clamping technology



0.3 mm shank diameter

TIRILBLOIS mini sets a benchmark in micro machining

less than **3** μ run-out accuracy

TIRILBLOIS-SVL Super-slim tool extension optimized interfering contours



up to **85,000** rpm

TIRILBLOIS-S predestined for high-speed cutting

... in your Automated Assembly



180% better gripping force – mass ratio
EGP – The powerful electronic gripper for small components with integrated electronics

∞ combination options
SCHUNK Modular assembly system



25% greater gripping force
MPG-plus – The most powerful pneumatic miniature gripper in the market



110 picks per minute
PPU-E – The fastest pick & place unit in the market, PPU-P with 90 picks/min

d Assembly

... in your Service Robotics Application

Future handling



6 degrees of freedom
Powerball lightweight arm LWA 4P
The lightweight arm with the world's most compact performance. Used on mobile platforms.



less than **3** μ run-out accuracy
TIEINBLO-S-R with unique patented polygonal clamping technology



more than **35** years of experience in
TIEINBLO Hydraulic expansion technology. TIEINBLO, the original. With 29 interfaces, versatile, with 3 μ run-out accuracy

up to **80** bar coolant-proof or peripheral coolant
Versatile clamping range with GZB-S Intermediate sleeves



100% suitable for all SCHUNK toolholders
TIEINBLO-SVL Tool extension – optimized interfering contours and super-slim



2,000 Nm torque with $\varnothing$ 32 mm
TIEINBLO E compact for large volume cutting, boring, reaming, and threads



0 μ permanent run-out accuracy
TIEINBLO zero, perfect vibration damping, resulting in up to 50% longer service life



Your Automated Machine Loading





SCHUNK No. 1 Products for higher Productivity in **your Automated Machine Loading.**

By using our modules you will maximize your system productivity due to faster loading and changing processes. The systematic use of single modules from SCHUNK clamping technology and gripping systems pays off as single components and even more when used in combination.

It's time to use your machine's
full potential!

30% more productivity

75 kN holding force

300 kg payload capacity

SCHUNK No. 1 Products for higher Productivity for your Automated Machine Loading.



Automated loading of a milling machining center with the clamping pallet prepared on the set-up table. After the introduction of the clamping pin, the SCHUNK quick-change pallet module positions and clamps the pallet in seconds.

300 kg loading capacity


NSR

Robot Coupling for Pallet Handling

Process reliable, precise, and space-saving

Automated pallet loading redefined. The slim SCHUNK NSR lightweight coupling with minimized interfering contours works extremely close to the machine table. Low designs consisting of a module for stationary use and clamping pallet are easy to implement. This leaves a lot of space in the machine room for the workpiece and axis movements.

- Highest pull-in forces of up to 15,000 N
- Lightweight of 1.6 kg
- Transmittable torques of up to 600 Nm
- Integrated slide monitoring and pallet presence monitoring



90% faster gripper change

SWS Quick-change System

One system, two components.

The standardized SCHUNK quick-change system SWS establishes the connection between the gripping system and robots or gantries. For manual change, SCHUNK offers the HWS manual change system.



75 kN holding force

VERO[®]-S NSA plus Automated Palletizing System

Highly efficient automation

Positioned within seconds with a repeat accuracy of < 0.005 mm, SCHUNK NSA plus is the precision module for automated machine loading. Built very low, it leaves ample space in the machine room.



90% less set-up costs due to setting up during machining

Tombstones with VERO[®]-S Quick-change Pallet Module

Fundamental high performers

Three tombstone shapes. Extremely compact design. Ideally suited to the selected SCHUNK clamping device. Activate the full power potential of your horizontal machining centers.





30% more productivity due to automated machine loading

PZN-plus Gripper with GSW-B Spindle Interface

The clever productivity booster

Cuts set-up times and saves complex and expensive automated solutions. The SCHUNK gripper sits in a toolholder like a tool and can easily be changed into the spindle due to the standard interface. The result: fully automatic workpiece change only with the help of the axis movements of the machine tool.

PZN-plus gripper with flexible GSW-B-AGE Compensation Unit

Before it breaks

Excessive forces during automatic machine loading? The SCHUNK GSW-B-AGE yields, compensation for tolerances and inaccuracies in six degrees of freedom is the answer.

180° rotation

SRH Swivel Head

Precise rotation and long life span

Maximum automated system productivity for demanding rotation tasks. Modules in the SCHUNK SRH series have a consistently modular structure and comprise tried-and-tested SRU rotary modules in conjunction with SRH rotary corners, EDF electrical feed-throughs and MDF media feed-throughs.



30 seconds, and the machine room is clean.

RGG Cleaning Unit

Sparkling clean machine table

Can be used for workpiece and machine room. Fits on almost any conventional toolholder mountings with a diameter of 20 mm. Cleans using air or coolant. Simply put into the machine and reduce idle times.



4.9 kg maximum workpiece weight

Vacuum Gripper GSW-V

Making machine tools more productive

Universal, maintenance-free tool for handling a large variety of flat components. Due to the integrated Venturi nozzle, this SCHUNK gripper doesn't need additional parts to generate a vacuum.





Automated raw and finished part handling with the machine spindle.

0% electricity requirement

Magnetic Gripper GSW-M

Attracting pole position

Maximum system productivity due to lean automation. Whether it's metal sheets, bearing rings or workpieces with complex contours – the SCHUNK magnetic gripper handles anything ferromagnetic without making adjustments or the need to change fingers, and efficiently based on the machine's own axis without electricity.



12 sizes available

Beta Linear Axis


Dynamic and smooth-running

You can choose between roller guides and profiled rail guides, depending on the application. The Beta series enables economical axis applications with high requirements for dynamics and smooth running. Long strokes can also be achieved with this axis type.





Your Automated Handling System





SCHUNK No. 1 Products for higher Productivity in **your Automated Handling System.**

SCHUNK offers the world's largest program of grippers, rotary, and swivel modules, linear modules, and robot accessories. Handling and assembly processes in the field of automation require diversity in variations of modules, particularly if the standard components are combined with each other. Discover the unforeseen possibilities.

It's time to use your machine's
full potential!

More than **500** standard combinations for line and room gantries

90% faster gripper change

100% cycle increase

More than 500 standard combinations

Line and Room Gantries LPP/LPE/RPE

Standard gantries from a modular system

Pre-assembled for immediate start-up. Pneumatic or electric. These standardized configurations can be combined into customized gantries, saving up to 50% in investment, project planning, assembly and installation.

- 5 kg, 10 kg, and 20 kg payload
- 300 mm in to 1,500 mm X-stroke/Y-stroke
- 25 mm in to 500 mm Z-stroke



360° endlessly turning

ERM Electric Rotary Module

Extremely adaptable – integrates perfectly

The drive can be freely adjusted in 90° steps. In this way, the interfering contour of the SCHUNK rotary module can be optimally adjusted to the gantries or robots. Depending on the engine, the endlessly turning module has torques of up to max. 75 Nm. It can attain any intermediate positions and is designed for a maximum speed of up to 62.5 rpm.



The No. 1 in gripping

2-Finger Parallel Gripper PGN-plus-P of the Generation Permanent

The unique gripper with multi-tooth guidance and permanent lubrication

Highly precise handling, higher payload, higher gripping forces. Various options for special application cases.



Up to 1,750 N gripping force

EGA Long-stroke Gripper

Adaptable, robust, compact.

With adaptation possibilities for all commonly available servo motors, the SCHUNK EGA is the most versatile electric long-stroke gripper that can be used on the market. Easily integrated in the automation system control, all properties of the current system can be transferred to the module.



IP65 protection class

OPR Collision and Overload Protection

Rapid reaction

Particularly designed for the use on small robots. Due to the minimum reaction time, the SCHUNK OPR reliably prevents damages due to collisions or overloads.





Use of a SCHUNK SRU-plus rotary unit in handling and assembly for picking up and positioning small components.

100% cycle increase

SRU-plus 20-S Universal Rotary Actuator

The new benchmark

Increase cycle numbers by up to 100% compared to state-of-the-art rotary actuators of the same size. The SCHUNK high-speed module allows for swiveling times from 0.3 s and cycle numbers of up to 3,700 cycles per hour.



Performance Level d/SIL 3

EGN Safety Gripping System


Permanently live

With the SLS, SOS and STO functionalities, the SCHUNK EGN gripping system certified in accordance with DIN EN ISO 13849 enables safe human/machine collaboration. In emergency stop mode as well, the gripper remains energized for securely holding the workpiece.





Your Automated Assembly





SCHUNK No. 1 Products for higher Productivity for **your Automated Assembly.**

Wherever pick & place and assembly tasks place the highest demands on precision and economy, SCHUNK is the solution provider for perfect implementation. No matter whether partially or fully automatic. No matter which drive medium. The innovative SCHUNK components always get that little bit of extra power out of your processes.


It's time to use your machine's
full potential!

110 picks per minute

∞ combination options

3 compensation directions

SCHUNK No. 1 Products for higher Productivity for your Automated Assembly.



In small components handling and the automated assembly process, workpieces have to be supplied quickly and reliably to the workpiece carrier. Various SCHUNK pick & place solutions can be used for this, and can be employed quickly and flexibly depending on the assembly process.

6 degrees of freedom

FT 6-Axis-Force-Moment Sensors

The largest diversity of variations on the market

SCHUNK 6-axis force-moment sensors measure forces and moments of 6 components during applications such as polishing, deburring, and difficult milling operations.



100% precision fitting

SCHUNK Adapter Plates

The individual connection

SCHUNK adapter plates ensure a high fitting accuracy in the interaction of robot accessory modules and ISO flange interfaces.



250 rpm endless turning

ERS Electric Rotary Module with DDF

Compact and extremely modular

Compact electric rotary module with integrated pneumatic and electric feed-through.



Compensation in 3 directions

TCU Compensation Unit

Optimal mounting or joining position

For automated joining or gripping of precise components. The SCHUNK TCU compensation unit compensates in X-, Y-, and Z-direction, corrects angle errors, and achieves rotational compensation.



110 picks per minute

PPU-P and PPU-E Pick & Place Units

The fastest in their class

With 110 picks per minute, the servo-electric SCHUNK PPU-E is the fastest pick & place unit in the market. SCHUNK PPU-P keeps up a brisk pace pneumatically with 90 picks per minute. Both are the ultimate in high-speed assembly work.

- 2 kg – 5 kg payload
- 10 microns repeat accuracy
- Plug & Work makes start-up as easy as can be



∞ combination possibilities

SCHUNK Modular Assembly System

More individuality and economy

Comprehensive, top class modular system for individual solutions. Benefit from the variety of components for automated assembly that have been tried and tested 100,000 times.



Up to 75 cycles per minute

DRL Rotary Pick & Place Unit

High-speed assembly with integrated rotary motion

Highly dynamic yet steady pick & place operations with rotating angles of 90° or 180°. The DRL is a specialized trendsetter for modular high-performance assembly in the SCHUNK program.



Over 10,000 possible combinations

Pillar Assembly System

The heart of the design in the most extensive modular program in the world

Unique pillar assembly system with numerous standardized pillar profiles, adapter plates, centering and connection elements. With more than 10,000 possible combinations, it is the most extensive modular program in the world for high-performance assembly.



6 sizes available

LDN Linear Module

For high-precision high-speed applications

Powerful servo motors can achieve a high rated force even in smaller modules. Alternatively, higher masses can be moved in vertical applications.





Up to 6 parts per cycle

RVK Collection Gripper

With 4 or 6 grippers

The SCHUNK RVK increases the productivity of pick & place applications by the collect & place principle. It collects the parts directly one after another, brings them collectively to the assembly or placement locations and puts them down there one after another.

- Collect & place principle is very easy to implement with RVK
- Minimizing cycle time and traverse paths
- Integrated valve technology
- Integrated electric feed-through for permanent monitoring of all grippers, leading to high process reliability.
- Simple mounting of the RVK on ERS 135, ERS 170 or RST-D 087 from SCHUNK

25% higher gripping force

Miniature Parallel Gripper MPG-plus

The benchmark

The most powerful miniature pneumatic gripper on the market. Ready for use around the world, wherever small parts need to be handled reliably and quickly. With its power density, the MPG-plus sets the new standard for handling small parts.



180% better gripping force/mass ratio!

EGP Electric Gripper for small components

The alternative

The most compact electric gripper for small components on the market. Based on the platform of the tried-and-tested pneumatic SCHUNK MPG-plus. The SCHUNK EGP makes changing from pneumatic to mechatronic gripping modules into child's play.



Swiveling time 0.18 s/180°

EGS Gripping Rotary Unit

Efficiency class in handling small parts

The most compact electrical gripping rotary unit in the world. The SCHUNK EGS combines electrical gripping and swiveling in the most compact space within a single housing. The angle of rotation can be defined freely between 40° and 320°, and can be set directly on the module as the gripping force can.



340° rotation range

Powerball ERB

Well-rounded and intelligent

The unique SCHUNK rotary module with swiveling/tilting function combines high torque and precision in the smallest of spaces. With up to 34 Nm and a weight of 3 kg, the SCHUNK ERB sets benchmarks in mechatronic integration.



The SCHUNK RVK collection gripper increases the efficiency of pick & place applications many times over by the collect & place principle in automated assembly.

50% higher moment load

DDF 2 Rotary Feed-through

Flexibly rotating up to 360°

The latest standard for modern robot and assembly applications. With 3 variants, the DDF 2 offers full flexibility for different process requirements. You have the choice: Pneumatic feed-through, feeding through of electric signals or the combination of both.



High torque 29.3 Nm

RST-D Ring Indexing Table

Versatile with power!

The SCHUNK RST-D for modular high-performance assembly possesses any amount of power for larger structures and up to six optional pneumatic feed-throughs. The pitch can be set to 4, 6, 8, 12 or even 16 steps as desired.



4 air feed-throughs

CWS Manual Change System

Manually fast

The SCHUNK CWS flat and weight-reduced manual change system ensures a fast change of grippers at the robot when re-equipping for a new range of parts. A noticeable increase in productivity can thus be achieved in particular for small and medium batch sizes.



Suitability for cleanroom applications ISO class 6

LM Linear Module

Standard solution for high-precision applications

The linear modules of the LM series are equipped with pre-loaded junction rollers in hardened prismatic running rails as guides. This precision guidance system guarantees absolute freedom from play in the overall system and offers high load capacities in all directions.





Your Service Robotics Application





SCHUNK No. 1 Products for higher Productivity in **your Service Robotics** Application.

Inspection systems, applications on mobile platforms, human to machine and human to human interaction. On the economic side of things, service robotics is becoming increasingly dynamic. Our mechatronic products are setting new standards in both professional and private spheres. SCHUNK is pushing development forward.

It's time to use your machine's
full potential!

> 7 degrees of freedom

100% flexibility

340° rotation range



SCHUNK Mobile Gripping Systems for higher Productivity in your Service Robotics Application.

SCHUNK is working intensively on numerous service robot projects worldwide. Due to the battery operation, our revolutionary developments are predestined for mobile platforms and independent. Their progress is documented by field-tested applications and projects in the research and testing phase.





Renovation Work

Sandblasting robots take over the dangerous and harmful maintenance of the Sydney Harbour Bridge. The core of the robots are SCHUNK LWA 4 lightweight arms in pressurized protective casings.

New Products

Your Automated Machine Loading

Your Automated Handling System

Your Automated Assembly

Your Service Robotics Application



Quality Assurance

The LWA 4P is a highly flexible handling device for a fully automated laboratory system at ThyssenKrupp AG. The 6-axis Powerball lightweight arm from SCHUNK is equipped with a mechatronic PG 070 gripper, and handles sensitive cement samples.



Laboratory Use

SCHUNK mobile gripping system components are used for new automation solutions in laboratory environments of the pharmaceutical and chemical industry.



Microchip Production

By using SCHUNK lightweight robots, our customized solutions provide flexible linking in industrial production. This example shows a mobile robot, carrying out transportation tasks such as loading and unloading in cleanroom conditions.



Exploration

The remote-controlled robot developed by the Harris company makes it possible to safely remove hazardous materials. As a manipulator, a modular lightweight arm based on SCHUNK PRL-plus modules is used.



Future Service Robotics

Wrists and the 1-finger-hand from the standardized module program for mobile gripping systems from SCHUNK ensure for mobile handling of the Care-O-bot® 4 of the Fraunhofer Institute for Production Technology and Automation IPA.



Rehab and Care Robot

The battery-powered SCHUNK LWA 4D lightweight arm has 7 degrees of freedom. Service robots developed by researches at the University of Bremen, help people with disabilities to achieve more independence.



6 degrees of freedom

Powerball Lightweight Arm LWA 4P

A lightweight arm with the world's best compact performance

The arm has three ideally integrated Powerball modules, offering 6 degrees of freedom. Integrated intelligence makes powerful, mobile handling possible as never before, especially in terms of human-robot cooperation.

- Weight/load capacity ratio of 2:1
- Gripping radius of over 700 mm
- Excellent repeat accuracy of 60 µm
- 24 V DC supply for mobile applications
- For every mobile platform – independent of the manufacturer

First industrial 5-finger hand

SVH 5-Finger Gripping Hand

An extremely wide range of sensitive gripping operations

The industrial version of the anthropomorphic SCHUNK SVH 5-finger hand grips nearly as perfectly as the human hand. Due to the integrated control in the wrist, the SCHUNK SVH can accomplish almost all of the movements of the human hand.



120 N gripping force

WSG 2-Finger Parallel Gripper

Configured in 2 minutes

Sensitive handling. This sensitive gripper communicates via Profibus DP, CAN or Ethernet TCP/IP. Due to an integrated web server and tactile sensors, handling tasks of the future are simple.



100% flexibility

SDH-2 3-Finger Industrial Hand

Using people as its model

The SCHUNK 3-finger industrial hand features maximum flexibility when it comes to the shape, size, and above all, position of the gripped parts. Form-fit and force-fit gripping with integrated tactile sensors make it a sensitive helper.



Height 14 mm

FWS Manual Change System

Extremely flat

The SCHUNK FWS flat manual change system is used where it is important to have the shortest possible clearance between the robot arm and tool, and the weight should be low.





Two SCHUNK LWA 4P lightweight arms take over the complete handling from separating out parts through to loading the machine in two separate systems. They can be moved on a linear axis or along passive rails.



10 degrees of freedom


LWA 4D Dextrous Lightweight Arm

From mine detectors to the latest in rehabilitation systems. The SCHUNK lightweight arm LWA 4D sets standards and can be found on service robots all over the world – often combined with our sensitive gripping systems.





Your Lathe





SCHUNK No. 1 Products for higher Productivity in **your Lathe.**

From powerful chucks, precision toolholders, and the world's largest standard chuck jaw program up to customized chuck jaw and hydraulic expansion toolholder solutions. SCHUNK always offers you the appropriate product.

It's time to use your machine's
full potential!

< 60 seconds quick jaw change

50% larger clamping range

0.01 mm repeat accuracy

SCHUNK No. 1 Products for higher Productivity in your Lathe.



The power chuck ROTA NCF plus 2 is the precise powerhouse for modern turning operation. The integrated centrifugal force compensation ensures save clamping at high RPM.

Sold more than **10,000** times

ROTA-S *plus* 2.0

Manual Chuck

The new generation

Its predecessor ROTA-S plus has already been sold by SCHUNK 10,000 times. The new generation ranks high due to: Higher rpm and cutting speeds due to permanently high clamping forces. Convenient jaw change in less than a minute due to optimized jaw quick-change system. Faster to use due to maximum operator safety. The ten-thousand-fold proven concept has now been perfected. It sets the standard.

- High jaw change repeat accuracy
- 3-fold base jaw securing
- More convenience through sensible accessories such as expansion arbor and changeable protection sleeves



60 seconds quick jaw change

ROTA THW *plus*

Power Chuck

Quick to adapt

The set-up time killer as of batch size 1. Quickly adaptable to a whole variety of clamping jobs due to jaw change in less than a minute.



410 kN clamping force

ROTA NCO

Power Chuck

Bursting with power

The specialist for rough machining with a large jaw stroke and long life span. Does the job that others give up on. Up to 410 kN clamping force.



0.01 mm repeat accuracy

VERO-S NSL turn

Quick-Change Pallet System

Set-up timer killer for mill/turn centers

Safe clamping even below a speed of 2,000 rpm. Very simple connecting interface with a repeat accuracy of 0.01 mm turns the module for stationary use into a turbo productivity station.



Clamping range **4 – 460** mm

ZENTRICO THL plus

Steady Rests

Highly precise with a long service life

A plus for any lathe in shaft machining. Excellent centering and repeat accuracy combined with maximum clamping forces. Integrated hydraulic cylinder with a large clamping range. For all around precision.




SCHUNK No. 1 Products for higher Productivity in your Lathe.



16,000,000 chuck jaws sold world-wide

With more than 1,200 different types, this is the world's largest standard program of chuck jaws for any lathe chuck application. More than 16 million standard chuck jaws have been delivered by SCHUNK since 1966 and are in use all over the world.



50% larger clamping range

SCHUNK Claw Jaw

Even more bite!

Unbeatable when it comes to transmitting high torques. The sharp serrations quickly claw into the workpiece surface and clamp them safely in one go. The possible combinations of basic, intermediate and top jaws expand the standard components' range of application by up to 50%.



3° maximum deflection possible

Pendulum Jaws

Intelligent yielding

As strong as necessary, as flexible as possible. Thin-walled workpieces can be clamped safely, without being deformed and at low-cost with standardized SCHUNK pendulum jaws with 6- or 12-point clamping. Within very little time conventional 3-jaw chucks can be re-equipped, to allow for 6-point clamping.



60,000 customized chuck jaw solutions

SCHUNK Chuck Jaws in special design

For complex clamping tasks

Modified SCHUNK standard jaw or complex special design. Perfectly customized, ideal solutions. As individual as necessary. As economical as possible.




30 - 40% less wear

Universal Base Jaw for Wedge-Bar Chuck

Honing for precision

Exclusive at SCHUNK: Base jaws – hardened and precision ground. Frequent top jaw changes easily cause wear on both components if the locating surface is not ground. SCHUNK base jaws stand for maximum repeat accuracy, perfect power transmission and longevity.





With more than 1,200 types, SCHUNK offers the world's largest range of standard chuck jaws. The right solution for your clamping task.

Up to **300%** improved
surface finish

T|E|N|D|O^{TURN} Hydraulic Expansion Toolholder

Including vibration damping!


The only modular SCHUNK hydraulic expansion toolholder that requires no manufacturer-specific interface. Unique vibration damping for excellent workpiece surfaces.

Two inserts: DSE double vise for true run-out and repeat accuracy of < 0.003 mm. DKE lathe clamping insert for increased productivity with the equipment at hand.





Your Machining Center





SCHUNK No. 1 Products for higher Productivity in **your Machining Center.**

Innovative and highly precise toolholding systems in the SCHUNK Total Tooling program featuring the largest modular system of stationary workholding cover a unique range of machining requirements.

It's time to use your machine's
full potential!

0 interfering contour

0 μ permanent run-out accuracy

0.3 mm shank diameter

SCHUNK No. 1 Products for higher Productivity in your Machining Center.



MAGNOS square pole technology for deformation-free clamping and the TENDO E compact hydraulic expansion toolholder for increasing the tool life by up to 300%.

Up to **300%**
longer tool life*

T | E | N | D | O® E compact Hydraulic Expansion Toolholder


Full power

The ultimate for large volume cutting. Convincingly priced, it makes it easy for you to change from mechanical and thermal toolholders to the more precise SCHUNK TENDO quality.

- Highest torques up to 2,000 Nm (with a diameter of 32)
- Run-out accuracy and repeat accuracy < 0.003 mm
- Up to 40% raised tool life

* Verified in a study by the wbk Institute of Production Technology at the Karlsruhe Institute of Technology (KIT).

Milling at
full speed!



www.schunk.com/tendo-e-compact



100% suitable

T | E | N | D | O® SVL Tool Extension

Long and super-slim

The innovative, SCHUNK TENDO SVL tool extension with optimized interference contours from SCHUNK sets new standards in regard to set-up time and costs. The extension is clamped into any SCHUNK toolholder within seconds. The SCHUNK TENDO SVL has been designed for and is suitable for the precise machining of hard-to-reach areas.



0 μ permanent run-out accuracy

T | E | N | D | O® zero Hydraulic Expansion Toolholder

Down to 0.000 mm in no time

Your pro for tight tolerances during drilling, reaming and drill-finishing. Perfect whenever you require the ultimate in run-out accuracy. For even cutting action and minimum tool costs. Perfect vibration damping for up to 50% longer tool service lives. Minimal set-up costs due to fast, safe tool changes.



100%
pull-out safety

T | E | N | D | O® Aviation Hydraulic Expansion Toolholder

Pull-out safety lock – easy to use and economical.

The integrated pull-out safety lock ensures correct tool orientation and form-fit clamping on weld-on shanks. Micro creep movements are completely eliminated while maintaining extremely close form and position tolerances.



New!

0 Interfering contour

T | E | N | D | O® ES Hydraulic Expansion Toolholder

The powerhouse without interfering contour

First choice when power and every bit of machining area counts. Tool clamping is done directly in the mounting taper. The result is: maximum holding forces, run-out accuracy < 0.003 mm, and additional space in the machine room.





0.3 mm shank diameter

T|R|B|O|S®-Mini **Polygonal Clamping Technology**

The smallest, exchangeable precision toolholder

Used in the medical, dental, electrical engineering, watch and jewelry, countersunk electrodes, and mold making industries. SCHUNK TRIBOS-Mini sets the standards where miniaturization needs to be implemented economically. This tiny one for minimal shank diameters of 0.3 mm is the benchmark in micro machining. This tool allows for extremely precise applications.

- Run-out accuracy of < 0.003 at $2.5 \times D$
- Balancing grade G2.5 at 25,000 rpm or $Rev_{max} < 1 \text{ gmm}$
- Quick and easy tool changes

3 μ run-out accuracy

T|R|B|O|S®-R **Polygonal Clamping Technology**

Stable and precise

Ideal for volume machining through selectively optimized radial stiffness and clamping force and a run-out accuracy of $< 0.003 \text{ mm}$. A special chamber system dampens vibrations and allows for a better surface and longer tool life.



85,000 rpm

T|R|B|O|S®-S **Polygonal Clamping Technology**

Extremely slim design

Designed slimmer than any other known toolholder system on the market. Pre-destined for precise machining tasks in difficult to reach workpiece areas due to its run-out accuracy of $< 0.003 \text{ mm}$.



85,000 rpm

T|R|B|O|S®-RM **Polygonal Clamping Technology**

The small one for high-speed cutting

High radial stiffness due to small compact design and excellent run-out accuracy of $< 0.003 \text{ mm}$. SCHUNK TRIBOS-RM is the compact precision champion when it comes to high speed ranges of up to 85,000 revolutions of tools as of 3 mm.




3 μ run-out accuracy

T|R|B|O|S®-SVL **Tool Extension**

Better price due to standardization

Super-slim tool extension, made for highly precise machining of difficult to reach areas. Flexibly combined with standard toolholders and tools, an SCHUNK SVL saves you from buying expensive special tools.





Intermediate sleeves from SCHUNK provide greater flexibility in tool clamping.

Coolant-proof up to **80 bar** or peripheral coolant

GZB-S Universal Intermediate Sleeve

Systematic cooling

Versatile application with SCHUNK TENDO, SCHUNK TRIBOS and SCHUNK SINO-R in the clamping range of 3 to 25 mm. Six coolant slots make the difference. SCHUNK intermediate sleeves with their innovative peripheral coolant allow you to keep cool when it comes to high-precision machining.



SCHUNK No. 1 Products for higher Productivity in your Machining Center.



Pocket milling with TENDO toolholder in aluminum plate, securely clamped by PLANOS vacuum clamping technology.

5-sided workpiece machining in one set-up

MAGNOS

Square Pole Technology

Economy cubed

Due to the level positioning of the workpieces on the SCHUNK MAGNOS magnetic chuck, all of the five workpiece sides are easily accessible and can be machined from all sides in one set-up.

Increased tool life and process reliability

Consistent permanent magnetic holding force across the entire workpiece effectively minimizes vibrations and leads to improved surfaces and noticable greater precision.

Minimum set-up times and increased productivity

The workpiece is clamped in seconds. Fine adjustment of the clamping elements or re-clamping the workpiece in the machining process are no longer required, nor are time-consuming set-up times and machine shutdown times.



100% encapsulated

KONTEC KSK Centric Clamping Vise

When the going gets rough

100% encapsulated. Fully functional in rough environments. Nothing keeps the sealed SCHUNK centric clamping vise from doing its job. No soiling. No jammed chips.



More than 75,000 implemented customized solutions

Customized Hydraulic Expansion Technology

For tool or workpiece clamping. SCHUNK offers customized hydraulic expansion tool-holders when standard solutions have reached their limits even for extreme requirements.



0.01 mm clamping precision

TANDEM[®] Clamping Force Blocks

Enormous power with highest precision

There is room for power in the smallest machining area. In confined spaces these compact versions with high clamping forces and a maximum repeat clamping accuracy of 0.02 mm ensure precise results.




±0.03 mm height tolerance

PLANOS Vacuum Clamping Technology

For process-reliable clamping

For fast and process-reliable clamping of flat-surface workpieces with an even underside. Even mechanically difficult to clamp components are clamped perfectly easy and deformation-free.



90% less set-up costs

VERO-S

Quick-Change Pallet System

The thriving one in the SCHUNK system

The set-up time killer for higher machine running times and a more rational production with batch sizes starting at one. Discover the ideal clamping solution for your machine.

- 90% less set-up costs
- With maximum pull-in forces of up to 40,000 N
- Repeat accuracy of < 0.005 mm



4-fold clamping station
VERO-S NSL plus 400 incl.
4 NSE plus 138 quick-change
pallet modules



2-fold clamping station
VERO-S NSL plus 200 incl.
2 NSE plus 138 quick-
change pallet modules



6-fold clamping station
VERO-S NSL plus 600 incl.
6 NSE plus 138 quick-
change pallet modules



8-fold clamping station
VERO-S NSL plus 800 incl.
8 NSE plus 138 quick-change
pallet modules

More than 500 variations for workpiece clamping

VERO-S

Quick-Change Pallet System

The largest modular system for individualists

SCHUNK VERO-S clamps workpieces, pallets, clamping stations, and tombstones via one or more clamping pins. It offers the best clamping solution for every machine. Raised modules offer additional flexibility. With SCHUNK almost everything can be clamped – precise down to the micron and according to your individual needs.



Combination with
SCHUNK TANDEM system



Combination with
SCHUNK KONTEC system



Combination with SCHUNK
MAGNOS magnetic clamping technology



Combination with
SCHUNK ROTA chuck



Combination
with SCHUNK tombstones

Due to many combination possibilities with various clamping devices or other equipment, and the fact that workpieces can be set up outside the machine in parallel to the processing time, a consistent application of VERO-S offers a set-up cost reduction of up to 90%.

Height 20 mm

VERO-S NSE mini Quick-Change Pallet System

Super-thin design

At a height of 20 mm, the SCHUNK quick-change pallet system VERO-S NSE mini is extremely thin. It is an expert in direct workpiece and pallet clamping, and in assembly. Ideal for smaller machines and simpler machining jobs.



2-fold, 4-fold or X-fold

VERO-S NSL mini Quick-Change Pallet System

Variability due to the modular system

Whether as a 2-fold, 4-fold or multiple clamping station – SCHUNK VERO-S NSL mini can be adapted to any individual requirement. For any application. On all conventional machine tables.





Germany – Head Office

SCHUNK GmbH & Co. KG
Spann- und Greiftechnik
Bahnhofstr. 106 – 134
74348 Lauffen/Neckar
Tel. +49-7133-103-0
Fax +49-7133-103-2399
info@de.schunk.com
www.schunk.com



Great Britain, Ireland

SCHUNK Intec Ltd.
Cromwell Business Centre
10 Howard Way
Interchange Park
Newport Pagnell MK16 9QS
Tel. +44-1908-611127
Fax +44-1908-615525
info@gb.schunk.com
www.gb.schunk.com



Russia

SCHUNK Intec 000
ul. Samojlovaj, 5, lit. C
St. Petersburg 192102
Tel. +7-812-326-78-35
Fax +7-812-326-78-38
info@ru.schunk.com
www.ru.schunk.com



Austria

SCHUNK Intec GmbH
Friedrich-Schunk-Strasse 1
4511 Allhaming
Tel. +43-7227 223 99-0
Fax +43-7227 210 99
info@at.schunk.com
www.at.schunk.com



Hungary

SCHUNK Intec Kft.
Széchenyi út. 70. | 3530 Miskolc
Tel. +36-46-50900-7
Fax +36-46-50900-6
info@hu.schunk.com
www.hu.schunk.com



Singapore

SCHUNK Intec Pte. Ltd.
25 International Business Park
#03-51/52 German Centre
Singapore 609916
Tel. +65-6240-6851
Fax +65-6240-6852
info@sg.schunk.com
www.sg.schunk.com



Belgium, Luxembourg

SCHUNK Intec N.V./S.A.
Industrielaan 4 | Zuid III
9320 Aalst-Erembodegem
Tel. +32-53-853504
Fax +32-53-853504
info@be.schunk.com
www.be.schunk.com



India

SCHUNK Intec India Private Ltd.
80 B, Yeshwanthpur, Industrial Suburbs
Bangalore 560022
Tel. +91-80-40538999
Fax +91-80-40538998
info@in.schunk.com
www.in.schunk.com



Slovakia

SCHUNK Intec s.r.o.
Levická 7 | SK-949 01 Nitra
Tel. +421-37-3260610
Fax +421-37-3260699
info@sk.schunk.com
www.sk.schunk.com



Brazil

SCHUNK Intec-BR
Av. Santos Dumont, 733
BR 09015-330 Santo André – SP
Tel. +55-11-4468-6888
Fax +55-11-4468-6883
info@br.schunk.com
www.schunk.com



Italy

SCHUNK Intec S.r.l.
Via Barozzo | 22075 Lurate Caccivio (CO)
Tel. +39-031-4951311
Fax +39-031-4951301
info@it.schunk.com
www.it.schunk.com




South Korea

SCHUNK Intec Korea Ltd
#1207 ACE HIGH-END Tower 11th,
883 Gwangyang-dong | Dongan-gu,
Anyang-si, Gyeonggi-do 431-804 | Korea
Tel. +82-31-382-6141
Fax +82-31-3826142
info@kr.schunk.com
www.kr.schunk.com



Canada

SCHUNK Intec Corp.
370 Britannia Road E, Units 3
Mississauga, ON L4Z 1X9
Tel. +1-905-712-2200
Fax +1-905-712-2210
info@ca.schunk.com
www.ca.schunk.com



Japan

SCHUNK Intec K.K.
45-28 3-Chome Sanno
Ohta-Ku Tokyo 143-0023
Tel. +81-3-37743731
Fax +81-3-37766500
info@jp.schunk.com
www.jp.schunk.com



Spain, Portugal

SCHUNK Intec S.L.U.
Foneria, 27 | 08304 Mataró (Barcelona)
Tel. +34-937 556 020
Fax +34-937 908 692
info@es.schunk.com
www.es.schunk.com



China

SCHUNK Intec Precision Machinery Trading
(Shanghai) Co., Ltd.
Xinzhuang Industrial Park,
1F, Building 1, No. 420 Chundong Road,
Minhang District
Shanghai 201108
Tel. +86-21-54420007
Fax +86-21-54420067
info@cn.schunk.com
www.cn.schunk.com



Mexico

SCHUNK Intec S.A. de C.V.
Calle Pirineos # 513 Nave 6
Zona Industrial Benito Juárez
Querétaro, Qro. 76120
Tel. +52-442-211-7800
Fax +52-442-211-7829
info@mx.schunk.com
www.mx.schunk.com



Sweden

SCHUNK Intec AB
Morabergsvägen 28
152 42 Södertälje
Tel. +46-8 554 421 00
Fax +46-8 554 421 01
info@se.schunk.com
www.se.schunk.com



Czech Republic

SCHUNK Intec s.r.o.
Drážní 7b | 627 00 Brno-Slatina
Tel. +420-531-022066
Fax +420-531-022065
info@cz.schunk.com
www.cz.schunk.com



Denmark

SCHUNK Intec A/S
c/o SCHUNK Intec AB
Morabergsvägen 28
152 42 Södertälje Sweden
Tel. +45-43601339
Fax +45-43601492
info@dk.schunk.com
www.dk.schunk.com



Netherlands

SCHUNK Intec B.V.
Speldenmakerstraat 3d
5232 BH 's-Hertogenbosch
Tel. +31-73-6441779
Fax +31-73-6448025
info@nl.schunk.com
www.nl.schunk.com



Switzerland, Liechtenstein

SCHUNK Intec AG
Im Ifang 12 | 8307 Effretikon
Tel. +41-52-35431-31
Fax +41-52-35431-30
info@ch.schunk.com
www.ch.schunk.com



Finland

SCHUNK Intec Oy
Hatanpään valtatie 34 A/B
33100 Tampere
Tel. +358-9-23-193861
Fax +358-9-23-193862
info@fi.schunk.com
www.fi.schunk.com



Norway

SCHUNK Intec AS
Hvervenmoveien 45 | 3511 Hønefoss
Tel. +47-210-33106
Fax +47-210-33107
info@no.schunk.com
www.no.schunk.com



Turkey

SCHUNK Intec Bağlama Sistemleri ve
Otomasyon San. ve Tic. Ltd. Şti.
Küçükyalı İş Merkezi, Girne Mahallesi
Irmak Sokak, A Blok, No: 9
34852 Maltepe | İstanbul
Tel. +90-216-366-2111
Fax +90-216-366-2277
info@tr.schunk.com
www.tr.schunk.com



France

SCHUNK Intec SARL
Parc d'Activités des Trois Noyers
15, Avenue James de Rothschild
Ferrières-en-Brie
77614 Marne-la-Vallée, Cedex 3
Tel. +33-1-64663824
Fax +33-1-64663823
info@fr.schunk.com
www.fr.schunk.com



Poland

SCHUNK Intec Sp. z o.o.
ul. Puławska 40A
05-500 Piaseczno
Tel. +48-22-7262500
Fax +48-22-7262525
info@pl.schunk.com
www.pl.schunk.com



USA

SCHUNK Intec Inc.
211 Kitty Hawk Drive
Morrisville, NC 27560
Tel. +1-919-572-2705
Fax +1-919-572-2818
info@us.schunk.com
www.us.schunk.com



Australia
Romheld Automation PTY. LTD.
Unit 30 | 115 Woodpark Road
Smithfield NSW 2164
Tel. +61-2-97211799
Fax +61-2-97211766
sales@romheld.com.au
www.romheld.com.au



Chile
Comercial Arnedo y CIA. LTDA.
Quinta Normal
Vargas Fontecilla # 4550 | Santiago
Tel. +56-2-7248123
Fax +56-2-7102036
caraneda@rotar.cl | www.rotar.cl



Colombia
Cav -
Control y Automatización Virtual Ltda.
43 Oficina 101 Avenida Esperanza N. 728
Bogotá D.C.
Tel. +57-1-6608719
Fax +57-1-4109846
info@cavingenieros.com
www.cavingenieros.com

MIKRA CAD CAM CAE, LTDA
AC-3 # 310-87, Bogota
Tel. +571-201-6379



Costa Rica
RECTIFICACION ALAJUELENSE, S.A.
100m al Oeste y 75m al Sur del
Cementerio Central de Alajuela, Alajuela
Tel. +506-2430-5111



Croatia
Bibus Zagreb d.o.o.
Anina 91 | 10000 Zagreb
Tel. +385-138-18004
Fax +385-138-18005
info@bibus.hr | www.bibus.hr

Okret d.o.o.
Majurina 16 | 21215 Kastel Luksic
Tel. +385-21-228449
Fax +385-21-228464
okret@okret.hr



Ecuador
ELIMED CIA. LTDA.
Calle El Progreso OE1-111 y Manglaralto
Quito
Tel. +59-39-7784740



Estonia
DV-Tools OÜ
Peterburi tee 34/4 | 11415, Tallinn
Mobile Phone +372-56-655954
Fax +372-6030508
info@dv-tools.ee



Greece
Georg Gousoulis Co. O.E.
27, Riga Fereou Str.
14452 Metamorfosi-Athens
Tel. +30-210-2846771
Fax +30-210-2824568
mail@gousoulis.gr | www.gousoulis.gr



Iceland
Formula 1 ehf
Breidamörk 25 | P.O. Box 1 61
810 Hveragerdi
Tel. +354-5172200 | Fax +354-5172201
formula1@formula1.is



Indonesia
PT. Metaltech Indonesia
Komplek Puri Niaga 1 Blok K7/IT
Puri Kencana | Jakarta Barat
Tel. +62-21-58350434
Fax +62-21-5918553
info@metaltechindonesia.com



Iran
Iran Int. Procurement of Industries Co.
(I.I.P.I.)
No. 10, First alley, Golshan St.,
Khoramshahr Ave. | Tehran, 1554814771
Tel. +98-21-88750965
Fax +98-21-88750966
info@iipico.com



Israel
Ilan and Gavish Automation Service Ltd.
26, Shenkar St. | Qiryat-Arie 49513
P.O. Box 10118 | Petach-Tikva 49001
Tel. +972-3-9221824
Fax +972-3-9240761
nava@ilan-gavish.com
www.ilan-gavish.co.il

M. K. Sales
Arimon 44 St. | Mosave Gealya 76885
Tel. +972-52-8283391
Fax +972-8-9366026
moti@mk-sales.com
www.mk-sales.com



Latvia
Sia Instro
Lacplesa 87 | Riga, 1011
Tel. +371-67-288546
Fax +371-67-28787
maris@instro.lv | www.instro.lv



Malaysia
Precisetech Sdn. Bhd
Plant 1, 15 Lorong Perusahan Maju 11
13600 Perai | Prai Penang
Tel. +604-5080288
Fax +604-5080988
sales@precisetech.com.my
www.precisetech.com.my

SK-TEC
Automation & Engineering Sdn. Bhd
No. 54-A, Jalan PU7/3,
Taman Puchong Utama
47100 Puchong
Selangor Darul Ehsan
Tel. +603-8060-8771
Fax +603-8060-8772
jeffery.koo@sk-tec.com.my
www.sk-tec.com.my



Peru
ANDES TECHNOLOGY S.A.C.
Avenida Flora Tristan 765
Lima
Tel. +51-1-3487611

MAQUINAS CNC, S.A.C.
Los Jazmines #143, Lima
Tel. +51-1-2750649



Philippines
Bon Industrial Sales
35 Macopa St. | Sta. Mesa Heights
Quezon City
Tel. +63-2-7342740
Fax +63-2-7124771
bonind@skyinet.net



Romania
S.C. Inmaacro S.R.L.
Industrial Machines and Accessories Romania
Avram Iancu Nr. 86
505600 Sacele-Brasov
Tel. +40-368-443500
Fax +40-368-443501
info@inmaacro.com
www.inmaacro.com



Saudi Arabia
Alruqee Machine Tools Co. Ltd.
Head Office
P.O. Box 36 57 | Alkhobar 31952
Tel. +966-3-8470449
Fax +966-3-8474992
mailbox2@alruqee.com
www.alruqee.net



Singapore
BALLUFF ASIA PTE LTD
18 Sin Ming Lane
#06-41 Midview City
Singapore 573960
Tel. +65-625-24384
Fax +65-625-29060
balluff@balluff.com.sg
www.balluff.com.sg

Eureka Tools Pte Ltd.
194 Pandan Loop, # 04-10 Pantech,
Industrial Complex | Singapore 128383
Tel. +65-687-45781
Fax +65-687-45782
eureka@eureka.com.sg
www.eureka.com.sg



Slovenia
MB-Naklo Trgovsko Podjetje D.O.O.
Toma Zupana 16 | 04202 Naklo
Tel. +386-42-771700
Fax +386-42-771717
mb-naklo@mb-naklo.si
www.mb-naklo.si



South Africa
AGM Maschinenbau Pty. Ltd.
42 Sonneblom Road, East Village
Sunward Park 1659, Boksburg
Tel. +27-11-913-2525
Fax +27-11-913-2994
alfred@agm-machinery.com
www.agm-maschinenbau.co.za



South Korea
Mapal Hiteco Co., Ltd.
1NA-502, Shihwa Ind. Complex 1254-10,
Jungwang-dong, Shihung-city
Kyunggi-do, 429-450
Tel. +82-1661-0091
Fax +82-31-3190-861
hiteco@kornet.net | www.hiteco.co.kr



Taiwan
Accudyna Engineering Co., Ltd.
2 F, No. 885, Youn-Chun East 1st. Rd
40877 Taichung City
Tel. +886-4-23807888
Fax +886-4-23805511
sales@accudyna.com.tw
www.accudyna.com.tw

Yonchin Enterprises, Inc.
5F, No. 100, Hsing Der Rd.
San Chung City 241, Taiwan
Tel. +886-2-2278-9330
Fax +886-2-2278-9320
yon.chin@msa.hinet.net
www.yonchin.com



Thailand
Brainworks Co., Ltd.
18/6, Soi Ram-intra 65, Tha-Rang
Bangkhen, Bangkok 10220
Tel. +66-2-5105908
Fax +66-2-5105903
chatchai@brainworks.co.th
www.brainworks.co.th



Ukraine
Center of Technical Support „Mem”LLC
Malysheva str.,11/25
Dnipropetrovsk 49026
Tel. | Fax. +38-056-378-4905
maxim.bayer@gmail.com
www.ctp-mem.com.ua



Lauffen/Neckar

SCHUNK GmbH & Co. KG | Spann- und Greiftechnik
Bahnhofstr. 106 - 134 | 74348 Lauffen/Neckar
Tel. +49-7133-103-0
Fax +49-7133-103-2399
info@de.schunk.com | www.schunk.com



Brackenheim-Hausen

SCHUNK GmbH & Co. KG | Spann- und Greiftechnik
Wilhelm-Maybach-Str. 3 | 74336 Brackenheim-Hausen
Technical Sales +49-7133-103-2503
Technical Support +49-7133-103-2696
Fax +49-7133-103-2189
automation@de.schunk.com | www.schunk.com



Huglfing

SCHUNK Montageautomation GmbH
Auwiese 16 | 82386 Huglfing
Member of SCHUNK Lauffen
Tel. +49-8802-9070-30
Fax +49-8802-9070-340
info@de.schunk.com | www.schunk.com



Mengen

H.-D. SCHUNK GmbH & Co. Spanntechnik KG
Lothringer Str. 23 | 88512 Mengen
Tel. +49-7572-7614-0
Fax +49-7572-7614-1039
futter@de.schunk.com | www.schunk.com



St. Georgen

SCHUNK Electronic Solutions GmbH
Am Tannwald 17 | 78112 St. Georgen
Tel. +49-7725-9166-0
Fax +49-7725-9166-5055
electronic-solutions@de.schunk.com | www.schunk.com

Your local technical consultant
www.schunk.com/services/ansprechpartner/aussendienst



International



Morrisville/North Carolina, USA

SCHUNK Intec Inc.
211 Kitty Hawk Drive | Morrisville, NC 27560
Tel. +1-919-572-2705
Fax +1-919-572-2818
info@us.schunk.com | www.us.schunk.com

Copyright

All text drawings and product illustrations are subject to copyright and are the property of SCHUNK GmbH & Co. KG

Technical Changes

The data and illustrations in this catalog are not binding and only provide an approximate description. We reserve the right to make changes to the product delivered compared with the data and illustrations in this catalog, e.g. in respect of technical data, design, fittings, material and external appearance.

Gripping Systems



☐ Complete Program Gripping Systems



☐ Grippers



☐ Rotary Modules



☐ Linear Modules



☐ Robot Accessories



☐ Product Overview



☐ Highlights New Products



☐ Product Overview Mechatronics



☐ Product Overview Linear Modules



☐ Product Overview Robot Accessories

Clamping Technology



☐ Complete Program Clamping Technology



☐ Toolholders



☐ Stationary Workholding



☐ Lathe Chucks



☐ Chuck Jaws



☐ Magnetic Clamping Technology



☐ Product Overview



☐ Hydraulic Expansion Technology Special Solutions



☐ Vacuum Clamping Technology



☐ Highlights New Products

Company	Name	Department
Street	ZIP	City
Tel.	Fax	E-Mail



Reg. No. 003496 QM08

Nr. 1

for precise gripping
and safe holding.



J. Lehmann

Jens Lehmann, German goalkeeper legend,
SCHUNK brand ambassador since 2012
for precise gripping and safe holding.
www.gb.schunk.com/Lehmann

852 minutes without a
goal against him in the
Champions League

681 minutes without a goal
against him in the national team

2 intercepted penalties
in the 2006 World Cup

1 headed goal as a goalie

0 defeats English Soccer Champion

and

More than **2,000,000**
sold precision toolholders

About **1,000,000**
delivered SCHUNK grippers

More than **100,000**
lathe chucks and stationary
workholding systems are in use
worldwide

More than **16,000,000**
sold standard chuck jaws

More than **75,000**
implemented hydraulic expansion
customer-specific solutions

SCHUNK GmbH & Co. KG
Spann- und Greiftechnik

Bahnhofstr. 106 - 134
D-74348 Lauffen/Neckar
Tel. +49-7133-103-2503
Fax +49-7133-103-2189
grippingsystems@de.schunk.com
www.schunk.com



www.youtube.com/SCHUNKHQ



www.twitter.com/SCHUNK_HQ



www.facebook.com/SCHUNK.HQ