





ROTA NC02

**Large 3-jaw power lathe
chucks for vertical lathes**

Weight-optimized large chucks with long jaw stroke. Optionally available with centrifugal force compensation or individual jaw adjustment

The ROTA NC02 has been specially developed for vertical lathes. Higher workpiece weights can be clamped thanks to the weight-optimized chuck body. The long jaw strokes combined with high clamping forces enable workpieces with a large interfering contour to be clamped in a reliable process. As an option, the chucks can be equipped with centrifugal force compensation and individual jaw adjustment in order to run at higher speeds or to optimally align complicated workpieces to the clamping center.



Advantages – Your benefits


- + Precision wedge-hook power lathe chuck for highest quality requirements**
Allows excellent machining results
- + High efficiency of the wedge hook system**
Process-reliable clamping due to high clamping forces
- + Optimum jaw support for O.D. and I.D. clamping due to a very long base jaw guidance**
Allows high clamping forces at a long service life
- + Optimized lubrication system**
Consistently high clamping forces ensured
- + Longest jaw stroke at high jaw clamping force**
Reliable and variable clamping of workpieces over interfering contours
- + Sealed against coolant and chips as standard via wiper strips, seals and sealed through-hole**
Excellently suitable for the use on vertical lathes
- + Low height design**
Maximum use of the machine room and maximum rigidity of the system
- + Weight-optimized cast body**
Reduced energy consumption and higher workpiece weights possible
- + Optionally available with centrifugal force compensation**
Less clamping force loss at high RPM
- + Optionally available with individual jaw adjustment**
Workpieces can be optionally aligned to the rotation center

Technical data

Description	Max. rotational speed [min ⁻¹]	Max. clamping force [kN]	Max. actuating force [kN]	Stroke/jaw [mm]	Piston stroke [mm]
ROTA NC02 800	900	300	170	23	57
ROTA NC02 1000	700	300	170	23	57
ROTA NC02 1200	600	300	170	23	57
ROTA NC02 1400	500	300	170	23	57

Function of ROTA NC02


The axially movable piston transfers the force to the base jaw and generates a radial jaw movement synchronized with the rotational axis.



- 1 Wedge hook drive**
Offers constantly high clamping forces in operation
- 2 Optimized lubrication system**
For consistently high clamping forces
- 3 Mounting thread**
For workpiece stops or cover plates
- 4 Additional slot guidance on the chuck face**
For workpiece stops or cover plates
- 5 Long jaw guidance**
Offers optimal support for O.D.- and I.D. clamping
- 6 Low height design**
Expands your machine's workspace
- 7 Combined sealing strips**
Seal the base jaw guidances and offer a good protection against coolant and chips
- 8 Individual jaw adjustment as option**
Workpieces can be optionally aligned to the rotation center
- 9 Module 2 serration**
For easy setting up and cleaning


Individual jaw adjustment (optional)

Due to individual jaw adjustment, the jaws can be adjusted individually and independently of each other. This ensures reliable clamping of both, angular and asymmetrical or rotationally symmetric workpieces.



Combined sealing strips

The combination of the scraper bar and the scraper plate resting against the base jaw provides excellent protection against penetration of chips and coolant.





- 6

Technical data

Spindle type	Spindle size	ID	Serration	Centrifugal force compensation	individual jaw adjustment	individual jaw adjustment [mm]	Moment of inertia [kgm ²]	Weight [kg]
-	Nr. 28 (Z720)	1481323	Modul 2				200	824
-	Nr. 28 (Z720)	1486024	Modul 2	●			200	824
-	Nr. 28 (Z720)	1481324	Modul 2		●	30	205	849


Scope of delivery

Chuck, T-nuts or mounting screws for top jaws, chuck mounting screws, eye bolt, and operating manual

Further technical data

Chuck type	Max. rotational speed [min ⁻¹]	Max. clamping force [kN]	Max. actuating force [kN]	Stroke/jaw [mm]	Piston stroke (H) [mm]
ROTA NC02 1400	500	300	170	23	57

Clamping force-RPM-diagram




Required minimum clamping force F_{spmin} 33%

SP-HB-M 1000
30.45 kg

SWB-M 1000
31.8 kg



Load of base jaw guidance



$M_{max} = 16800 \text{ Nm}$

T-nut




NS
T-nut

Chuck type	Description	ID	N	B	H	H1	L	Cyl.-screw	Max. adm. tightening torque
			[mm]	[mm]	[mm]	[mm]	[mm]		[Nm]
ROTA NC02 1400	NS 240-2	0140124	30	42	41	15	34	M24 x 60	450


Our complete range of chuck jaws can be found online in our Chuck Jaw Quickfinder and on [schunk.com](https://www.schunk.com)

Soft top jaws

Modul 2



SWB-M
Soft top jaws



SWBL-M
Soft top jaws


Technical data

Chuck type	Description	ID	N [mm]	B [mm]	H [mm]	L [mm]	a [mm]	b [mm]	m/SET [kg]
ROTA NC02 1400	SWB-M 1000	1506279	30	80	105	195	100	60	31.8
ROTA NC02 1400	SWBL-M 1000	1506303	30	80	105	258	148	60	40.3

Our complete range of chuck jaws can be found online in our Chuck Jaw Quickfinder and on [schunk.com](https://www.schunk.com)

Hard stepped top jaws

Modul 2



SP-HB-M
Hard stepped top jaws


Technical data

Chuck type	Description	ID	N [mm]	B [mm]	H [mm]	L [mm]	T [mm]	a [mm]	b [mm]	c [mm]	m/SET [kg]
ROTA NC02 1400	SP-HB-M 1000	1506315	30	80	105	250	22	89.2	60	60	30.4

Our complete range of chuck jaws can be found online in our Chuck Jaw Quickfinder and on schunk.com

Claw jaws

Modul 2



SZA-M
Claw jaws

Technical data

Chuck type	Clamping range ØD	Swing diameter SDmax	Description	ID	N	B	H	L	T	G	b	Screws	m/SET
	[mm]	[mm]			[mm]	[mm]	[mm]	[mm]	[mm]		[mm]		[kg]
ROTA NC02 1400	119 - 1087	1463	SZA-M 80-1	1563497	30	80	105	204	42	M10	60	M24	23.4
ROTA NC02 1400	450 - 1333	1449	SZA-M 80-2	1563516	30	80	105	163	42	M10	60	M24	18.3

Our complete range of chuck jaws can be found online in our Chuck Jaw Quickfinder and on [schunk.com](https://www.schunk.com)

Hard stepped top jaws

Modul 2



Jaw position I

Jaw position II

O.D. clamping

Chuck type	Description	ID	A1 [mm]	A2 [mm]	A3 [mm]	A4 [mm]
ROTA NC02 1400	SP-HB-M 1000	1506315	45 - 831	100 - 986	276 - 1161	440 - 1326

I.D. clamping

Chuck type	Description	ID	I1 [mm]	I2 [mm]	I3 [mm]
ROTA NC02 1400	SP-HB-M 1000	1506315	212 - 989	372 - 1155	545 - 1330

Accessories

Clamping force tester

For measuring the jaw clamping force of 2, 3 and 6-jaw chucks up to 6,000 RPM.



Suitable for	Description	ID
ROTA NC02 1400	IFT Set	1404235

Extension set for large chucks

For use as an extension of the IFT measuring head for measuring the jaw clamping force of large chucks of Ø 400 mm and more.



Suitable for	Description	ID
ROTA NC02 1400	IFT adapter set	1498512

Grease

LINOMAX plus

High-performance grease as standard for regularly lubricating SCHUNK manual and power lathe chucks and steady rests.



Bundle	Description	ID
Cartridge	LINOMAX plus cartridge	1342585
Can	LINOMAX plus can	1342586
Bucket	LINOMAX plus bucket	1342587

Grease gun

Auxiliary tools for lubrication of all kinds of SCHUNK products. The grease gun can be used for cartridges of all types of SCHUNK grease.



Bundle	Description	ID
Cartridge	Grease gun	9900543



**H.-D. SCHUNK GmbH & Co.
Spanntechnik KG**

Lothringer Str. 23
D-88512 Mengen
Tel. +49-7572-7614-1300
Fax +49-7572-7614-1039
CMM@de.schunk.com
schunk.com